

iluminar

IR148-2 Series

Product Features

- Short range IR illuminator
- SMT LED technology
- Distances up to 148' (45m)
- Angles 10°, 30°, 60°, 100° & 120°
- 850nm or 940nm Wavelengths
- Low power consumption (15W)
- Long life
- 5 year warranty
- IP67 weatherproof rating
- Built-in photocell IR on/off
- Telemetry input for remote switching
- 12 or 24VDC or 24VAC input



What is IR Illumination?

Active or near infra-red (NIR) illumination is energy which is invisible to the human eye but can be seen by a high quality true day/night camera (IR cut filter removed). The energy from IR illuminators resides just outside the visible red section of the electromagnetic spectrum, above 700nm and below 1000nm.

IR illumination is an ideal source of illumination for security cameras for the following reasons.

- It is invisible to the human eye but visible to black/white and true day/night cameras.
- Avoids the problem of light pollution.
- Longer range than visible light

All Iluminar illuminators provide superior IR lighting for video surveillance systems. They are available with a range of angles to cover different distances and scenes.

Supplied with an IP67 rating, they are vandal proof and can be used indoors and outdoors. The anodized aluminum housing provides protection from the harshest weather conditions.

Professional Illuminators vs Camera Built-in Illuminators

There are many advantages of using separate, professional illuminators versus built-in camera infrared illuminators

- Longer life on the LED's
- No hot spots
- Wider angles
- Longer range
- Avoids attracting insects to obscure camera view

Models

Model Number	Wavelength	Angle	Distance		HOV	
IR148-A10-24-2	850nm	10°	148'	45m	26'	8m
IR148-A30-24-2	850nm	30°	82'	25m	43'	13m
IR148-A60-24-2	850nm	60°	62'	19m	72'	22m
IR148-A100-24-2	850nm	100°	51'	15m	117'	36m
IR148-A120-24-2	850nm	120°	43'	13m	148'	45m
IR148-C10-24-2	940nm	10°	69'	21m	13'	4m
IR148-C30-24-2	940nm	30°	39'	12m	20'	6m
IR148-C60-24-2	940nm	60°	30'	9m	32'	10m
IR148-C100-24-2	940nm	100°	24'	7m	55'	17m
IR148-C120-24-2	940nm	120°	20'	6m	69'	21m

General

Electronics	High efficiency surface mount high power LED's with advanced current limited integral control circuitry
Number of SMT LED's	4
Construction	Robust high quality aluminum extrusion
Front window	Polycarbonate high transmittance protective (vandal-proof) IR filter
Finish	Black anodized
Power Cable	9ft (3m)
Telemetry Following Contact	Via cable
Pressure Equalization Vent	Prevents thermal expansion & pressure cycling
Photocell	Adjustment via Remote
Illumination	Adjustable via Remote
Operating Temperature	-58° to 140°F (-50° to 60°C)
Weight	1.63lbs (0.5kg)
Mount	Black powder coated stainless steel wall mount
Dimensions	2.16" x 4.33" x 3.15" (55 x 110 x 80mm)

Electrical

Input Voltage	12 or 24V DC or 24V AC
Input Current	1.0A at 24Vdc/VAC 2.0A at 12Vdc
Consumption	15W

Wavelength

Standard (A)	850nm (semi-covert) Faint red glow visible on the illuminator only (no visible light)
Optional (C)	940nm (covert) No visible glow from illuminator – ideal for transportation or high security applications

Certifications

IP	IP67 in accordance with EN60529:1992
EMC	EN61000, FCC part 15.107 15.108 Class B
WEEE	Waste Electrical & Electronic Equipment European directive 202/96/EC
RoHS	Restriction of Hazardous Substances European directive 202/95/EC