

1038 series surface mount contacts

magnetic contacts with wire leads

The 1038 series contacts are designed for window and door applications where surface mounting is preferred.

Because of its sleek design, the 1038T contact is fast and easy to install. The switch and magnet are incorporated into the housing, and the terminal blocks are angled for easy access.

In the unlikely event that the switch needs replacing, just push the housing down and slide it off. This reduces replacement time and eliminates any damage to the mounting surface.



Specifications

| | |
|---------------------------|---|
| Voltage: | 100 VAC/VDC max. |
| Current: | 0.5 A max. |
| Power: | 7.5 W max. |
| Loop type: | Closed |
| Electrical configuration: | Normally open |
| Gap distance: | Up to 1 in. |
| Lead type: | 1 ft. #22 wire |
| Dimensions: | 2.26 x 0.38 x 0.40 in. (57 x 9.5 x 10 mm) |
| Housing: | Flame retardant ABS plastic |
| Color: | White, brown |
| Regulatory: | UL, CUL |

- Attractive, low-profile design
- Simple to install
- Easy to replace switch if needed

Ordering information

| | |
|----------------------|--|
| 1038N-10PKG (-50BOX) | Surface mount magnetic contact with wire leads, 1 in. gap size, closed loop, white, pk/10 (pk/50 -50BOX) |
| 1038M-10PKG | Surface mount magnetic contact with wire leads, 1 in. gap size, closed loop, brown, pk/10 |

