Black-and-White Camera KTC-105

Product Specification



The KTC-105 lets you use C- and CS-mount lenses.

he KTC-105 is an economical, black-andwhite general-purpose security camera that offers 380 lines of resolution and high sensitivity (.01 lux). The KTC-105 lets you use C- and CS-mount lenses. The KTC-105's selectable backlight compensation prevents important foreground objects from becoming silhouetted against bright backgrounds.

The camera includes a variable high-speed electronic shutter that

will compensate for conditions ranging from bright sunlight to lowlight conditions.

For the best results in situations with wide variations in lighting, such as outdoor applications or indoor applications that call on the camera to perform daytime and after-hours surveillance, we recommend an auto iris lens. The KTC-105's auto iris circuit lets you use both video and DC auto iris lenses.

Features

- 380 lines of resolution
- .01 lux sensitivity
- Utilizes variable high-speed electronic shutter
- Accepts video and DC auto iris lenses
- Lightweight miniature design



Black-and-White Camera KTC-105

Product Specification

Technical Specifications

Image Device 1/3" interline transfer CCD

Signal System EIA standard or optional CCIR

Picture Elements 542 H x 494 V (EIA) 542 H x 584 V (CCIR) 2:1 interlace

Scanning System 525 line 60 frame (EIA); optional 625 line 50 frame (CCIR)

Synchronizing System Internal

Resolution 380 TV lines

Sensitivity .01 lux (faceplate) .1 lux @ f1.2 (scene)

Signal-to-Noise Ratio >46 dB

Electronic Shutter 1/60 - 1/80,000 second, automatic adjustment

Video Output 1.0 Vp-p video into 75-ohm

Lens Mount C and CS mount

Auto Iris Lens Accepts video and DC auto iris lenses

Operating Temperature 14 to 122 °F (-10 to 50 °C) Power Source 12 VDC

Power Consumption 1.9 W


Gray Scale Minimum 10 shades

Geometric Distortion

Control (Switch) ELC: on (EE)/off (AI) Iris Control: ALC (DC/video) BLC: on/off

Humidity 0 to 95% relative

Weight 7.3 oz (207 g)



Mailing Address

PMB 225, P.O. Box 3004 Corvallis, OR, USA 97339 www.kalatel.com **Americas** toll free 800-469-1676 tel 541-754-9133

fax 541-754-7162

Asia tel 852-2907-8108 fax 852-2142-5063 **Australia** tel 61-3-9259-4700 fax 61-3-9259-4799

Ħ

Π



Document: 1036002B / May 2001

© 2001 Kalatel. As a company of product innovation, Kalatel reserves the right to change product specifications without notice. See your Kalatel Sales Representative for revised specifications.