

Features:

- Durable 3mm polycarbonate case
- Fully sealed and enclosed electronics
- Up to three tamper protection devices:

Cover removal

Removal of unit from wall

Cover screw removal (optional extra)

- Piezo sounder provides up to 118dB(A) sound level at 1m
- High visiblity xenon strobe giving excellent visual alarm signal
- Dual flashing comfort LEDs
- Optional SCB mode of operation enables sounder to operate from internal battery power, allowing several units to be connected to a single control panel without risk of overloading the panel power supply
- Adjustable sound option allows individual units to be identified in multiple unit installations
- Complete with 8.4V NiMH backup battery
- Selectable 9 or 15 minute cut-off timer to conform with noise abatement guidelines
- 3 year warranty

Flashguard Sounder products come with the following benefits:

- FREE Technical helpline
- Comprehensive logo design and screen printing service
- Fully BS4737 compliant
- Compatible with any control panel
- Fully weather resistant to IP55
- Conformally coated electronics for complete protection against moisture
- Simple to install:

5 second first fit test feature eliminates need to make more than one trip up the ladder

Fixing screw kit provided
Drilling template on carton

Specification:

Sounder type: Single piezo (second piezo available as optional extra)

Sounder output level @ 1m: 118dB(A) Strobe frequency: 1Hz