



5MP Day & Night Fixed Dome Camera



Features

- 5 megapixel CMOS image sensor
- Video without compression, no delay with high quality and real-time monitoring.
- 2D noise reduction
- DWDR function
- High efficiency IR LED, radiant distance up to 16m
- Day & Night (IR cut removable)
- Long transmission distance–Coaxial cable
- Seamless compatibility with the standard Analog equipment
- UTC function (AHD-Coaxial protocol)
- Video Output: AHD 5MP or CVBS 960H

Specifications

| | |
|---|---|
| Model | AHD755A3.6 |
| Min. illumination/Low Light Mode (Colour) | Color 0.08 Lux at F2.0 B/W 0 Lux with IR LED ON |

| | |
|-------------------------------|---|
| Video output | AHD / CBVS / TVI / CVI |
| Resolution | 2,560(H) x 1,920(V) @20fps |
| Focal Length | 3.6 mm |
| Iris | F2.0 |
| Angle of View | 84.1°(H) 62.3°(V) 111.5°(D) |
| Beam Spread | 60° |
| Infrared LED Wave Length | 850nm |
| Max IR distance | 16M |
| Pick Up Element | 1/2.5" CMOS Image Sensor |
| Effective pixels | 2,608(H) x 1,952(V) |
| Starting Temperature | 0°C – +50°C (32°F – 122°F) |
| Operating temperature | -10°C – +50°C (14°F – 122°F) |
| Storage temperature | -25°C – +60°C (-13°F – 140°F) |
| Operating humidity | 0% – 90% RH |
| CE | Yes |
| Scanning System | Progressive Scan |
| Sync. Mode/ Synchronization | Internal |
| Infrared Cut Filter | Auto / Day (Color) / Night (Mono) / Ext |
| S / N Ratio | More than 55dB (AGC off) |
| 3D Noise Reduction | 2D DNR |
| 2D WDR | Off / On |
| UTC | UTC (AHD-Coaxial protocol Supported) |
| Auto Gain Control | Auto |
| White Balance | ATW / MANUAL |
| Electrical Shutter | 1/30(1/25)s – 1/60,000s : Auto |
| Back Light Compensation (BLC) | Yes |
| Dimensions | Ø93 × 74(H) mm |
| Weight | 230g |
| Color | White |
| Power Supply | DC12V ±10% |
| Power Consumption | 4.8W |

