

HOUSING & BRACKET

Camera Housing / Camera Bracket

Camera Bracket




Speed Dome Bracket



PIH 5040S / 5063 / 5084

Housing & Bracket





Camera Housing

Outdoor Housing			
Product Picture			
Model	PIH-5040S	PIH-5063	PIH-5084
Mounting	Bottom		
Construction	Aluminum		
Window Dimension Glass Thickness	74(W) x 64 (H) / 5mm	Φ110 Heat Resistant Glass / 5mm	Φ78 Heat Resistant Glass / 3mm
Dimension	140mm(W) x 115mm(H) x 373mm(D)	Housing : Φ134 x 318mm (L) Bracket : 211.5mm (L)	Housing : Φ112 x 384mm (L) Bracket : 211.5mm (L)
Weight	1.3kg	2.0kg	1.9kg
Ext. Model	-	PIH-5063 : AC230V (Heater & Blower) PIH-5064 : AC24V (Heater & Blower) PIH-5067 : AC117V (Heater & Blower)	PIH-5084 : AC24V (Heater) PIH-5088 : AC90~260V (Heater)



PRH 5480 / 5880 / 5480M / 5880M / 54200 / 58200 PRH 9480 / 9880

IR Housing

Infrared Illuminator Housing				Invisible Infrared Illuminator Housing				
Product Picture								
	Inside Look							
Model	PRH-5480	PRH-5880	PRH-5480M	PRH-5880M	PRH-54200	PRH-58200	PRH-9480	PRH-9880
Power Input Voltage	AC24V ±10%	AC90 ~ 260V max.	AC24V ±10%	AC90 ~ 260V max.	AC24V ±10%	AC90 ~ 260V max.	AC24V ±10%	AC90 ~ 260V max.
Radiant Distance	100m		60m		200m		80m	
Window	Φ110 Heat Resistant Glass							
Glass Thickness	3mm							
Infrared LED	Wave Length		850nm				940nm	
	Angle		10° + 30°		30°		6° + 30°	
	Quantity		11 units (10°) + 6 units (30°)		17 units		5 units (6°) + 2 units (30°)	
	Power On		Sensor Auto Control, Adjustable Control Point					
Blower Control	On:35°C Off:25°C							
Heater Control	On:15°C Off:25°C							
Suitable Camera and Lens	Max. 200mm length							
IP Rating	IP66							
Mounting	Bottom							
Construction	Aluminum							
Power Consumption	22W				32W			
Operating Temperature	-40°C~+60°C (-40°F~140°F)							
Dimension	Housing : Φ134 x 318mm (L), Bracket : 211.5mm (L)							
Weight	3500g							



PIH 500 / 500L / 5001N / 5002L / 5005M / PIH 5004 / 5004L

Camera Bracket

Bracket							
Product Picture							
Name	Camera Bracket						
Model	PIH-500	PIH-500L	PIH-5001N	PIH-5002L	PIH-5005M	PIH-5004	PIH-5004L
Adjustment	Pan: 360° Tilt: ±90°			Pan & Tilt	Pan: 360° Tilt: ±90°	Pan & Tilt	Pan & Tilt
Maximum Load	2kg			6kg	5kg	10kg	10kg
Construction	ABS Injection			Aluminum		Aluminum, Light Gray Textured	
Dimension(mm)	76 (W) x 153 (H) x 73 (D)	76 (W) x 218 (H) x 73 (D)	123 (L) x 45 (Φ)	202 (W) x 252 (H) x 24 (D)x 119 (Φ)	164 (L) x 119 (Φ)	85 (W) x 309 (H) x 99 (D)	61 (W) x 240 (H) x 83 (D)
Weight	80g	100g	110g	700g	280g	600g	300g



PIH WM / 26WM / BTR01S / 5003 / BTS02S

Camera Bracket

Bracket						
Product Picture						
Name	Camera Bracket			Scanner Bracket	Corner/ Pole Mount	Camera Bracket
Model	PIH-WM	PIH-26WM	BTR01S	PIH-5003	BTS02S	BTR03S
Adjustment	-	-	Pan & Tilt	Pan	-	-
Maximum Load	5kg	2kg	10kg	10kg	15kg	2kg
Construction	Aluminum, creamy white textured	ABS injection	Aluminum	Aluminum, white light gray textured textured	Aluminum, silver gray baked enamel finish	Iron, silver gray baked enamel finish
Dimension(mm)	132 (W) x 111 (H) x 169 (D)	120 (W) x 65 (H) x 144 (D)	262 (W) x 287 (H) x 39 (D)	85 (W) x 309 (H) x 99 (D)	190(W) x 130 (H) x 105 (D)	200(W) x 50(H) x 52(D)
Weight	600g	95g	1000g	450g	500g	300g



PIH 303B / 303PEX / 303P / PIH-510 CPM / PIH Z6 / 520HB / 76WM / 303BX

Speed Dome Bracket

Bracket								
Product Picture								
Name	Wall Mount	-	Pendant Mount	Corner/ Pole Mount	-	Pendant Mount	Wall Mount	Wall Mount
Model	PIH-303B	PIH-303PEX	PIH-303P	PIH-510 CPM	PIH-Z6	PIH-520HB	PIH-76WM	PIH-303BX
Maximum Load	30kg	-	30kg	25kg	-	-	5kg	30kg
Construction	Aluminum, Light Gray Textured					Aluminum		Steel, Light Gray Textured
Dimension(Mm)	148(W) x 385 (H) x 175 (D)	300(H)	148(W) x 385 (H) x 175 (D)	275(W) x 91 (H) x 182(D)	300(H)	284(L)x204(W) x149.5(H)	150(W) x110 (H) x 171 (D)	180(W) x 318.5 (H) x 214 (D)
Weight	1.2kg	-	1.1kg	0.5kg	-	2.7Kg	0.5kg	3.9kg
Schematic Drawing		-			-			



PIH 520L / 520LB / CPM / 520G / 510L / 510H

Speed Dome Bracket

Bracket						
Product Picture						
Name	Wall Mount	Wall Mount	Corner/ Pole Mount	Swan Neck	Wall Mount	Pendant Mount
Model	PIH-520L	PIH-520LB	PIH-CPM	PIH-520G	PIH-510L	PIH-510H
Maximum Load	-	-	20kg	-	-	-
Construction	Aluminum			Steel	Aluminum	
Dimension(mm)	100(W) x160 (H) x 210(D)	204(W) x284(H) x 255(D)	156.6(W) x126 (H) x 86.8(D)	725(L)x455(W)x83(H)	405(W) x367.15(H) x 270(D)	274(W) x477.5(H) x 270(D)
Weight	0.84kg	3.1kg	0.44kg	6.8kg	5kg	4.8kg
Strap	-		Stainless Strap for Pole X2	-		
Schematic Drawing						