



---

## 20X Day & Night 60fps Full HD PTZ Dome IP Camera



---

### Features

- Outdoor PTZ camera
- 20X optical zoom
- IP66 rain and dust resistant
- IR cut filter for day/night operations
- 1080p resolution
- Wide Dynamic Range up to 90dB
- H.264 and Motion JPEG multi-profile video streaming

---

### Description

The PSD4624EX20 is 1080P HD PTZ Dome IP Camera featuring 20X optical zoom capability . The high-speed dome is capable of streaming HD video at up to 60 frames per second. Featuring Wide dynamic Range (WDR) feature, the PSD4624EX20 captures highlights and shadows simultaneously, eliminating pixilation and smear. Capable of making 360° continuous rotations, users can accurately position the camera to identify specific targets. PSD4624EX20 PTZ camera provide IP66-rated protection against water and dust. With built-in heaters and fans, the cameras are able to be used in temperatures ranging from - 40°C – + 50°C. The 20X optical zoom gives the PSD4624EX20 an impressive range. With a focal length of 4.3mm (WIDE) – 86mm (TELE), PSD4624EX20 is ideal for numerous applications.

## Specifications

Model	PSD4624EX20
Min. illumination/Low Light Mode (Colour)	0.5 lux (1/30 sec, F1.6(Wide), 50IRE, AGC-Gain: 30dB ICROFF Color mode)
Lens zoom ratio	20X Optical
Focal Length	4.7 (WIDE) – 117.5 (TELE) mm
Minimum Aperture Ratio	1 : 1.6 (Wide) – 3.5 (Tele)
Iris Range	F1.6 – 32 , Close
Iris Control	DC IRIS , ALC ( Adjustable Output Target Level ) / Manual
Minimum object distance	30 cm (WIDE end), 1.5M (TELE end)
Angle of View	(H) 59.94°(W) – 3.30°(T) (V) 36.16°(W) – 1.87°(T)
Zoom Speed	0 – 7 Selectable [ Fast : Approx. 6.0 Second ( Tele to Wide ) in Manual Mode ]
Focus Speed	0 – 7 Selectable [ Fast : Approx. 6.0 Second ( Tele to Wide ) in Manual Mode ]
Focus	Auto ( Continue / Interval / Zoom Trigger / One Push), Manual Focus
Pick Up Element	1/2.8" CMOS image sensor
Effective pixels	1944 (H) × 1224 (V) = 2,379,456 (pixels)
CE	Yes, EMI CLASS A

FCC	Yes, EMI CLASS A
UL	Yes
IP Rating	IP66
Vandal Resistant Rating / IK Rating	IK10
Starting Temperature	- 40°C – + 50°C ( -40°F – 122°F )
Operating temperature	- 40°C – + 50°C ( -40°F – 122°F )
Storage temperature	- 20°C – + 60°C ( -4°F – 160°F )
Operating humidity	0% – 90%
Power Supply	AC24V ±10% / DC24V / PoE++ (IEEE 802.3bt)
Power Consumption	AC24V, 20W / DC24V, 32W / PoE++, 31.2W (Heater OFF) AC24V, 48W / DC24V, 51W / PoE++, 52.1W (Heater ON)
Control Function	Pan and Tilt / Zoom and Focus / Iris and ICR / 256 Preset Position / Home Position
Auto Mode	OFF / SCAN(16) / SEQ(256) / TOUR(16) / PATROL(16) / Auto TRACKING
Schedule Setting	OFF / SCAN (4)/ SEQ(256) / TOUR(4) / PATROL(4) / Preset Position(256)(via web interface)
Panning Range	360° Endless
Panning Mode	Manual , Auto , Manual Position , Sequential Position
Panning Speed	Manual Approx. 0.1°/s – 120°/s 8 Steps, Preset Approx. 1°/s – 360°/s, Alarm Trigger Speed 360°/s
Tilting Range	-6° – +186°
Tilting Mode	Manual , Auto , Manual Position , Sequential Position
Tilting Speed	Manual Approx. 0.1°/s – 120°/s 8 Steps, Preset Approx. 1°/s – 360°/s, Alarm Trigger Speed 360°/s
CPU	Intel® Core™ i3 or higher grade
OS	Windows 7 or above
RAM	4GB or above, Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9 or above

Dimensions	275 (H) × 192 (D) mm
Weight	2750 g
Casing Material	Aluminum alloy
Window / Glass Thickness	Transparent dome cover
Audio Input / Output	one audio input / one audio output Terminal block type (microphone not built-in)
Live Video Output	CVBS 1.0Vp-p, 75 ohm, terminal block type
Audio	G.711 u-law / PCM
Alarm Input / output	Digital 4 Input (TTL 5Vdc) , 2 Output (0.5A 120Vac, 1A 24Vac) , Terminal block type
Video Compression	H.264 Main and High Profile, Motion JPEG
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.264 and Motion JPEG, configurable frame rate and bandwidth
Video bitrate	128Kbps – 12Mbps, Frame rate and bit rate controllable on-the-fly, VBR / CBR / GOP supported; Fixed bitrate
Encryption	Base64 HTTP encryption
Authentication	Digest HTTP authentication, RTSP Authentication, IEEE 802.1x authentication
Address Filter	IP address filter, MAC address filter
Access	Multiple user access levels with password protection
User accounts	Multiple user access levels with password protection
Multi IP address	Yes
Resolution	2MP(1920 × 1080), 1.3MP(1280 × 960), 1MP(1280 × 720), D1(720 × 480, 720 × 576), VGA(640 × 480), CIF(352 × 240)
Maximum Frame Rate	Normal mode (H.264 / MJPEG) 60Hz: 60 FPS @ 1920 × 1080 50Hz: 50 FPS @ 1920 × 1080 WDR mode (H.264 / MJPEG) 60Hz: 30 FPS @ 1920 × 1080 50Hz: 25 FPS @ 1920 × 1080

Scanning System	Progressive scan
Infrared Cut Filter	Auto / Day (Color) / Night (Mono)
White Balance	ATW / Indoor(3200K) / Outdoor(5800K) / Manual(1800K - 10500K)
Back Light Compensation (BLC)	OFF / ON
Electrical Shutter	Auto / manual(1/30(25) - 1/10,000)
Exposure Mode	AUTO / IRIS.P / SHUT.P / MANUAL
Sense Up	OFF / ON
Sense Up+	Yes
Auto Gain Control	50dB Variable Gain
S / N Ratio	More than 50dB (AGC off)
3D Noise Reduction	OFF / ON (1 - 5)
High Dynamic Range(HDR)	Up to 90dB
Privacy Masking	OFF / ON ( Up to 16 area)
Image Effects	Contrast, Sharpness, Mirror, Flip, Defog, DIS, Digital Zoom(x16)
Mobile Application	Integrated to LILIN mobile app (LILIN Viewer) iPhone, iPad, Android support
Video Management	ONVIF Profile S, LILIN Navigator Enterprise 2.0, Third party VMS through LILIN HTTP API
SD Card (recording)	Support Micro SD/SDHC/SDXC (up to 128GB) card for circular recording (card is not included)
Maintenance	Firmware update via HTTP and IP Scan; Firmware available at web site
IVS Basic 1.0	Motion Detection, Tampering Detection, Advanced Motion Detection, Traffic Light Detection, Tripwire Detection, Object Counting
Alarm event triggers	Alarm(1 - 4) / Motion / Tamper / Audio / Network loss detection
Alarm event actions	FTP, SMTP, SD card, SAMBA, Alarm output(2), HTTP post, SNMP Trap, Preset position

Control interface	RS-485, Half-Duplex, support MLP2, Pelco D/P protocols
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Network Interface/Ethernet	10/100/1000Mbps Base-T, RJ-45
ePTZ & Digital Zoom	16X
PTZ Control	Pan , tilt , zoom in / out , absolute position, and video-click-nmove
OSD	Text overlay for date, time, and camera name, and PTZ position
CPU.Memory	Embedded SoC, 500MHz Dual ARM Cortex-A9 & 500MHz ARM11, 1GB DDR3, 256MB flash memory
Network OS	Embedded Linux 3.8.0
Protocols	IPv4, IPv6, TCP, UDP, HTTP, SMTP, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SIP, Bonjour, 802.1x
Max number of online users	10 user accounts available
Video Display	LILIN Universal ActiveX & HTML5