

Luxriot Mini NVR/DVR Series are optimized and designed to work with Luxriot VMS for sensitive data storage of IP/Megapixel Cameras and Analog Cameras.

Designed for use with Luxriot VMS



Mini IP NVR Server

LUXRIOT MINI NVR/DVR SERVER

Features:

- Hybrid IP & Analog
- Advanced Intel® Core™ i3-4130, i5-4570S & i7-4770S
- Internal HDD configurations 1TB, 2TB, 3TB & 4TB
- Motherboard Video Adapter with HDMI & DVI outputs
- 4 GB of DDR3 Kingston RAM
- Server is pre-installed with Windows® 7 OS on dedicated solid state drive*
- Advanced form factor ensures extremely quiet operation
- Built-in DVD-RW for high speed archiving

Optimized & Designed for:



Luxriot Models



Luxriot Mini NVR Models		
LUXR-MINI-SVR-1TB-i3	LUXR-MINI-SVR-2TB-i5	LUXR-MINI-SVR-3TB-SSDi7*
LUXR-MINI-SVR-2TB-i3	LUXR-MINI-SVR-2TB-SSDi5*	LUXR-MINI-SVR-4TB-SSDi7*
LUXR-MINI-SVR-3TB-SSDi3*	LUXR-MINI-SVR-3TB-SSDi5*	
LUXR-MINI-SVR-4TB-SSDi3*	LUXR-MINI-SVR-4TB-SSDi5*	

* Includes 120GB SSD for OS - Can add optional PCI-X Network Card or Capture Board to any Mini Server

● Specifications

Luxriot NVR Model	LUXR-MINI-SVR-1TB-i3	LUXR-MINI-SVR-2TB-i3	LUXR-MINI-SVR-3TB-SSDi3	LUXR-MINI-SVR-4TB-SSDi3	LUXR-MINI-SVR-2TB-SSDi5	LUXR-MINI-SVR-3TB-SSDi5	LUXR-MINI-SVR-4TB-SSDi5	LUXR-MINI-SVR-3TB-SSDi7	LUXR-MINI-SVR-4TB-SSDi7
Power Supply	(1) 300W Mini PSU (110~220V Selectable)								
Form Factor	Intel Chipset								
Cooling System	1 x 80mm Fan								
Operating System	Windows 7 (64 Bit) on 40GB Partitioned 1TB HD	Windows 7 (64 Bit) on 40GB Partitioned 2TB HD	Windows 7 (64 Bit) on 120GB Intel SSD						
NIC	(1) Internal Intel Gbit Ethernet 1000 Mbps LAN								
DVD/CD RW	Front Panel Access								
Storage	1TB	2TB	3TB	4TB	2TB	3TB	4TB	3TB	4TB
Chassis	Mini ATX Desktop								
Graphics Card	Integrated graphics support for processors with Intel® Graphics Technology (HDMI/DVI/VGA)								
CPU	i3-4130	i3-4130	i3-4130	i3-4130	i5-4570S	i5-4570S	i5-4570S	i7-4770S	i7-4770S
RAM	4 GB fully buffered								
Dimensions (W x D x H)	3.9" x 13.3" x 10.2"								

● Optional Capture Boards

Capture Boards	
HC7008L	FULL HEIGHT. 240FPS H.264 D1 at 30FPS/channel board PCI-X1 64Bit Driver- 8 channels Video - 8 channels Audio - 1 video out - 1 Audio out - On board motion detection - NTSC/PAL
HC7016XL	FULL HEIGHT. 480FPS H.264 D1 at 30FPS/channel board PCI-X1 64Bit Driver- 16 channels Video - 16 channels Audio - 2 video out - 2 Audio out - On board motion detection - NTSC/PAL