



Minidome

Imager	1/4" Interline Transfer CCD
Lens size	F1.8 ~ 2.8, f=3.8 ~ 38mm
Line resolution	500 TV Lines
No. of pixels (effective)	440K Pixels [752(H) x 582(V)]
Zoom - optical + digital	10x Optical Zoom and 10x Digital Zoom
Zoom - total	100x
Horizontal view angle	61.93° - 5.42°
Min sensitivity - colour	0.7 Lux (Day) @ 50 IRE
Min sensitivity - mono int	0.02 Lux (Night, DSS) @ 50 IRE
Focus/iris	Auto / Manual / Semi-Auto
Signal to noise ratio	50dB (AGC Off)
Picture freeze	Yes
Day & Night	Auto / Day / Night (IR Cut Filter)
Rotation speed	Preset : 360°/ sec Manual : 0.05°~ 360°/ sec (Zoom Proportional) Swing : 1°~ 180°/ sec
Range	Pan : 360°(Endless) / Tilt: 90°
Presets	128 Presets with Labels / Independent Preset Characteristic Setup
Tours	4
Swing	8 swing
Serial Port	RS 485
Power Supply	DC 12V / 1.0A
Operating temperature	0°C ~ 40°C / 32°F ~ 104°F
Dimension	Dome : ø 115 mm / 4.5" Housing : 165(ø) 160(H) mm / 6.5" (ø) 6.3" (H)
Mounting options	Wall Mount Bracket, Ceiling Mount, In-ceiling


Surface Mount



Flush Mount



Wall Mount



Ceiling Mount



MAIN FEATURES

- 100x Zoom Control (Optical 10x, Digital 10x)
- Day & Night (IR Cut Filter)
- SNR (Super Noise Reduction)
- Smooth Motion at High Zoom Magnification Mode
- Endless 360° Pan Rotation
- 8 Privacy Zone masking function
- On-Screen Display On/Off
- Small Size / Weather-proof / Vandal-Proof

2 year warranty

CIEFFE are continuously in research and development and therefore reserves the right to alter specifications and prices without notice. For precise information, please contact your CIEFFE representative. Subject to change in design and specifications. Subject to error.

CIEFFE S.p.A.

Via Lavoratori Autobianchi, 1
Edificio 23
20033 Desio - Milano - ITALY
phone +39 0362 17935
fax +39 0362 1793590

www.cieffe.com
info@cieffe.com

