

SE2 Pendant PTZ 30x

2MP PTZ for indoor and outdoor applications




Shown with wall mount/back box



Shown with short mount/back box









For customers who want to monitor a large area from multiple angles and perspectives with a single camera, the **SE2 Pendant PTZ 30x** from March Networks® provide uncompromising security, indoors or outdoors. The camera's integrated HDR, 30X zoom lens, P-Iris, and 2MP resolution guarantee superior image quality, regardless of lighting conditions.



Key Benefits

- 30X zoom lens.** Get a wide angle view of a large area with no distortion, and zoom in on distant objects, while maintaining clarity.
- High Dynamic Range (HDR).** The camera blends the best parts of several separate exposures together to combine the most focused, well-lit, and colorful parts of the scene.
- Image stabilization.** Reduces vibration and blurring, especially when the camera is zoomed all the way in, or is installed up high or in a windy area.
- Power Redundancy.** Combining PoE with AC or DC guarantees zero downtime; if power goes out, the camera switches to PoE with no interruption.
- Save money on storage and bandwidth.** When the camera is in its home position, its low bit rate (LBR) setting reduces storage and bandwidth usage by 50% or more in most applications; streams can drop below 2Mbps at 2MP (15 fps).

MOUNTING OPTIONS

 <p>1.5" NPT Short Pendant Mount with Back Box</p>	 <p>1.5" NPT Wall Mount with Back Box</p>	 <p>1.5" NPT Pendant Mount</p>
 <p>1.5" NPT Wall Mount</p>	 <p>Corner Adaptor</p>	 <p>Pole Adaptor</p>

Maximize your level of protection while minimizing your surveillance costs.

SE2 Pendant PTZ 30x

CAMERA	
Image Sensor	1/2.8" Sony CMOS
Effective Pixels	2MP; 1945 (H) x 1097 (V)
Lens	4.3 – 129 mm, F1.6, P-Iris
Field of View	H = 67°(wide), 2°(tele); V = 38°(wide), 1°(tele)
Signal / Noise Ratio	>50 dB
High Dynamic Range (HDR)	120 dB
Day/Night	Automatic IR Cut Filter
Minimum Illumination	Color: 0.02 lux @ F1.6 (50 IRE) B/W: 0.012 lux @ F1.6 (50 IRE)
Shutter Speed	1/10000s
Camera Angle Adjustment	Pan 360°, Tilt 180°, Rotation -100° to 100°
Optical Zoom	30X
White Balance	Manual/Automatic
VIDEO	
Video Compression	H.265, H.264, MJPEG
Resolution	2MP 1080p (1920x1080), 1MP 720p (1280x720), XGA, SVGA, D1, VGA, CIF
Frame Rate	Up to 30fps @ 2MP
Streaming	Up to four individually configurable streams in H.265, H.264, MJPEG Configurable resolution/frame rate/bandwidth; LBR/VBR/CBR bitrate modes available
Image Settings	Iris control, backlight compensation, white balance, noise reduction, wide dynamic range, privacy mask, brightness, exposure, sharpness, contrast, saturation, hue, IR configuration, day/night threshold
AUDIO	
Audio Streaming	Two-way, stereo
Audio Compression	G.711 PCM 8 kHz
Audio Input/Output	Line in/line out
NETWORK	
Security	Password protection, HTTPS encryption, IEEE 802.1X
Supported Protocols	Pv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, DHCP, PPPoE, QoS, ONVIF-S/G/T, SNMPv1/v2/v3
OPERATIONAL	
Pan Manual Control Speed	0.1° - 90°/second
Tilt Manual Control Speed	0.1° - 55°/second
Pan Preset Speed	400°/second
Tilt Preset Speed	300°/second
Pan Rotation Angle	360° continuous rotation
Tilt Rotation	-10° - 100°
Pan Preset Accuracy	0.225°
Tilt Preset Accuracy	0.225°
Programmable Presets	256
Programmable Patterns	8
Autopan	4
Sequence	8
Auto Home	Yes
Motion Detection	Yes (4 areas)

SYSTEM INTEGRATION	
Video Analytics	Video motion detection, privacy zones
Alarm Trigger	Motion detection, external input
Alarm Events	Video recording to local storage, external output activation
ELECTRICAL	
Power	PoE (IEEE 802.3at); 24VAC
Power Consumption	PoE: typical 26W; 24VAC: typical 2.3A
PHYSICAL	
Construction	Metal and plastic
Dimensions (H x D)	10.4 x 8.4 in (26.4 x 21.2 cm)
Weight	5.7 lbs (2.6 kg)
ENVIRONMENTAL	
Operating Temperature	13° to 131°F (-25° to 55°C)
Humidity	10 - 90% RH, non-condensing
Ingress Protection Rating	IP66
Impact Rating	IK10
GENERAL	
Local Storage	Full Size SD memory card up to 1TB (sold separately)
LED Indicator	Power, Activity
Included Accessories	Quick Start Guide; mounting template; mounting hardware; BNC video adapter
USER CONNECTIONS	
Alarm	4 x Alarm In, 2 x Relay Out
Audio	1 x Input, 1 x Output
Serial Communication	RS-485 Terminal block
Ethernet	RJ45 10/100 Base-T
Analog Video	1 x BNC Output
Power	Terminal block
REGULATORY	
Certification Model	C3702A
Safety	UL 62368-1, CSA 62368-1, IEC/EN 62368-1
Emissions	EN 55032, EN BS 55032, EN61000-3-2, EN BS 61000-3-2, EN61000-3-3, EN BS 61000-3-3, FCC Part 15 Subpart B, ICES-003, CISPR 32, AS/NZS CISPR 32
Immunity	EN50130-4, EN BS 50130-4
Environmental	RoHS3, WEEE
Compliance Marking	CE, cULus, RCM, WEEE, UKCA
ORDERING INFORMATION	
CAMERA	
39535-101	SE2 Pendant PTZ 30x (indoor/outdoor)
ACCESSORIES	
36990	1.5" NPT Short Pendant Mount with Back Box
HOMINIDOMESMA	1.5" NPT Pendant Mount
36989	1.5" NPT Wall Mount with Back Box
HOMINIDOMEWB	1.5" NPT Wall Mount
HOMINIDOMEPPMA	Pole Adaptor
27639	Corner Adaptor
37272	SE2 Pendant PTZ smoked bubble
40934	Single port, 60W, IEEE 802.3bt-compliant indoor PoE midspan

5-year warranty:

- Option for Advance Replacement or Repair & Return.
- No need to issue a PO prior to receiving the replacement.
- March Networks incurs all shipping costs – both ways – for Advance Replacements.

North America 1 800 563 5564
 Latin America +5255 5259 9511
 Europe +39 0362 17935
 Asia +65 6818 0963
 Australia and New Zealand +61 1300 089 419
 Middle East and Africa +971 4 399 5525

© 2023 March Networks. All rights reserved. Information in this document is subject to change without notice. MARCH NETWORKS, March Networks Command, March Networks Searchlight, March Networks RideSafe, and the MARCH NETWORKS logo are trademarks of March Networks Corporation. All other trademarks are the property of their respective owners.
 060-3486-00-B
 marchnetworks.com

