



NID338

5-Megapixel Indoor Dome Camera

1/3.2" Lumii sensor, H.264, triple streaming, remote zoom and auto focus, ICR day/night, WDR, 3DNR, SDXC/SDHC card slot

The NID338 is a professional 5-megapixel IP dome camera designed for detail-demanding indoor surveillance, delivering high quality live view and recorded footage with superior high definition video up to 30fps. A true day/night camera, the NID338 features improved sensitivity backed by proprietary Lumii™ Low Light Technology and 3DNR to provide unprecedented image clarity under the cover of darkness. The NID338 also features installation-facilitating motorized zoom with auto focus, as well as enhanced WDR and local storage to make it a versatile solution for diverse indoor surveillance applications.



ONVIF



Motorized Lens for Remote Zoom and Auto Focus

The motor-driven zoom functionality enables configuration over the network to achieve the optimized viewing angle of the monitored area. Auto Focus can be also done with just one simple mouse click, simplifying the installation significantly for faster and easier setup.



Ultra Wide Dynamic Range

Compared with standard WDR, the new-generation WDR features sophisticated algorithm to further expand its dynamic range of the lighting conditions. It allows the camera capturing greater scene details in high contrast settings or in scenes with extremely bright and dark areas.



True Day/Night with Mechanical ICR

Featuring IR Cut Filter Removable (ICR) function, the camera is perfect for capturing truer color images at day time by filtering out IR. At night, IR is allowed for the camera working in B/W mode and being more sensitive to IR, thereby capturing clearer monochrome images.



Easy Installation with 3-axis Adjustment

An ideal feature for wide-area surveillance, the 3-axis angle adjustment makes camera installation easy, allowing installers to adjust the camera's direction and to level the image with ease whether it's mounted on walls or on ceilings.



3D Noise Reduction

The 3DNR technology takes traditional DNR a step further, removing digital artifacts and grainy appearance from frame to frame, while maintaining image sharpness at low light settings, which results in more efficient bandwidth utilization and less storage space consumption.

Specifications

Video	
Sensor Type	1/3.2" progressive scan CMOS sensor
Active Pixels	2592x1944 (HxV)
Compression	H.264 / MJPEG
Streaming	Triple simultaneous streams with multiple video profile
Resolution	2592x1944, QXGA(2048x1536), 1080P, 1280x960, 720P, SVGA(800x 600), VGA(640x480), 640x360, QVGA(320x240), 320x180
Max. Frame Rate	5MP 4:3 (2592x1944) at 12 fps 3MP 4:3 (2048x1536) at 15 fps 2MP Full HD 16:9 (1920x1080) at 30/25fps (NTSC/PAL)
Day/Night	Mechanical (ICR) D/N Control
Day/Night Mode	Auto/ BW/ Color
Shutter Time	1/10,000s to 1/7.5s Selectable (60Hz); 1/10,000s to 1/6.25s Selectable (50Hz)
Minimum Illumination	Color: 0.15 lux at 50 IRE, 0.03 lux at 10 IRE, F1.2; B/W: 0.03 lux at 50 IRE, 0.006 lux at 10 IRE, F1.2 (Shutter speed: 1/15 sec)
Video Output	NTSC: 720x480 @30fps; PAL: 720x576 @25fps
Bit Rate Control	CBR, VBR
Lens	
Lens Type	Built-in; Varifocal
Focal Length	f=3~9mm, F1.2
Focus / Zoom	Autofocus, motorized / Remote
View Angle	H: 78°(Wide)~28°(Tele)
IRIS Control	DC IRIS
Audio	
Audio Communication	Two-way Audio
Compression	G.711 PCM 8kHz, a/μ-law support
Audio In/Out	External microphone and speaker
Image Enhancement	
Image Settings	AES, AWB, AGC Exposure Mode: AES / ALC / Flickerless / Manual; White Balance: Auto / Manual; Backlight Compensation Configurable Brightness, Contrast, Hue, Saturation, and Sharpness Gamma Correction
WDR	Enhanced Digital WDR
DNR	Configurable 3DNR setting
Privacy Zone	Yes, up to 8 privacy zones
Image Orientation	Mirror, Flip
Frequency Control	NTSC(60Hz)/ PAL(50Hz)
Date & Time Stamp	Yes
Intelligent Video & Event Management	
Motion Detection	Yes, 3-level sensitivity
Ethernet Detection	Network loss detection
Others	Optimized i-frame (GOP) setting
Events	Motion detection, ethernet detection, external alarm
Event Actions	Event snapshot to remote FTP storage/ email recipients, Edge recording to SD card, HTTP event query, HTTP event client pulling

Store Category	Event snapshot, Edge recording, Manual Snapshot, Manual Recording
Local Storage	
Memory Card Slot	SDXC/SDHC card support
Memory Card Overwrite	Yes
Network	
Protocol	ARP, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, RTSP/RTCP/RTP, QoS, SMTP, SNMP, TCP, UDP, UPnP, IEEE802.1X
Ethernet	10Base-T/100Base-TX Ethernet connection for LAN / WAN, RJ-45
ONVIF	Yes
Browser	Internet Explorer, Chrome, Firefox, Safari
Security	Multiple user access levels with password protection; IP address filtering; IEEE 802.1X network access control, HTTPS encryption, and digest authentication
I/O & Controls	
Power	2-pin Terminal block/ Female RJ-45 10BASE-T/100BASE-TX PoE
Power LED Indicator	System power and status indicator
Alarm In/Out	Terminal block 1 in / 1 relay out (30V, 1A)
Network	RJ-45 with LED Indicator
Audio In/Out	Terminal block 1 in / 1 out
Analog Video	1 x composite video out, micro JST
System Reboot	Reset x 1
Factory Default	Default x 1, pressing 5 sec for loading factory default
Power	
Power Requirement	DC 12V & AC 24V ± 10% / PoE (IEEE 802.3af, class 0)
Power Consumption (Max.)	7W
Mechanical	
Dimensions(ΦxH)	Φ125mm x 106mm (Φ4.92" x 4.18")
Weight	500g (1.1 lb)
3-Axis	Yes
Pan/Tilt Adjustment	Pan: 0°-350°, Tilt: 15°-90°, Rotate: 0°-350°(Max.)
Environmental	
Operating Temperature	-10°C ~ 50°C (-14°F ~ 122°F)
Operating Humidity	90% RH, non-condensing
Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Regulatory	
Approvals	CE, FCC, RoHS
Ordering Information	
Model No.	NTSC: NID338-N5-MES; PAL: NID338-P5-MES
Accessories	Surface Mount: standard package support

Dimensions

