

ZoneVu Virtual Monitor Wall Specification

DIGITAL-IP ✓

ANALOGUE ✗

HYBRID ✓



Specification

Operating Temperature - 0°C to 40°C

Storage Temperature - -10°C to + 60°C

Operating Humidity - 10% to 95% non condensing

Enclosure - 4U 19" Euro rack. Aluminium and mild steel construction. Colour - Black

AC Power Input - 99 to 264VAC 50/60Hz tba VA

Cooling Fan - tba

Weight - Net tba

Dimensions - tba

MTBF - tba

Certification - UL, cUL, TUV, CE, FCC, RoHS

Serial Data Ports - RS232

Network Data Ports - 10/100/1G

CPU & Storage - 2 GHz 32-bit (x86) Quad-core processor, 2GB of system memory, 40 GB of SATA hard drive capacity with 15GB free space

Graphics - A directX 9 class graphics processor that supports a WDDM driver. Pixel shader 2.0 in hardware, 32 bits per pixel, PCIe 16x graphics bus, 256 MB of graphics memory and Dual monitor support (1280 x 1024)

Video - PAL 25fps; NTSC 30fps; MPEG-4; H.264; CIF; 2 CIF; 4 CIF and D1



The purpose of this data sheet is to provide product information on Meyertech products. The information in this datasheet is believed to be accurate and reliable. However, no responsibility or liability is assumed by Meyertech Limited for its use, or for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or other rights of Meyertech Limited. Meyertech are committed to continuous product development and therefore reserve the right to change specification without notice.

