

ZoneVu Virtual Matrix Manager Specification

DIGITAL-IP ✓

ANALOGUE ✗

HYBRID ✓



Specification

Temperature - Operating 0°C to +40°C, Storage -10°C to +60°C, Humidity 10% to 95% non condensing

Enclosure - 1U 19-Inch Euro Rack, Aluminium and mild steel construction

Colour - Black

AC Power Input - 99 to 264VAC 50/60Hz

Ac Power Consumption - 690VA, 6A @ 115V, 6A @ 230V

Cooling Fan - Four 4cm fans

Weight - Net -11Kg

Dimensions - 480.4 (W) X 474 (D) x 44 (H) mm

MTBF - 105,405 Hours

Certification - UL, cUL, TUV, CE, FCC, RoHS

Serial Data Ports - RS232

Network Data Ports - 10/100/1G

Operating System - Microsoft Windows Vista Business or XP Pro

Ordering Information

ZonveVu-VMM - ZoneVu Virtual Matrix Manager



The purpose of this data sheet is to provide product information on Meyertech products. The information in this datasheet is believed to be accurate and reliable. However, no responsibility or liability is assumed by Meyertech Limited for its use, or for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or other rights of Meyertech Limited. Meyertech are committed to continuous product development and therefore reserve the right to change specification without notice.

