

ZoneVu ZVS TVNP3 Server Specification

DIGITAL-IP ✓

ANALOGUE ✓

HYBRID ✓



Specification

Enclosure - Fully enclosed Euro rack. Colour - Black

Dimensions - 19" rack by 1U by 142mm

Weight - 10Kg

Power - 260W, 100-240V, 50-60Hz, 4 Amp Max

Operating System/Processor - Windows XP Professional/Intel Xeon 3050 2.13GHz

Operating Temperature - 10°C to 35°C

Operating Relative Humidity - 8% to 90% (non-condensing)

MTBF - 100,000 Hours

Connections - RS232 x 4 (1 x ZoneVu, 3 x TVNP), RJ45 LAN x 2 (Gigabit Ethernet), VGA,

USB (2.0 Compliant) x 4 (2 front, 2 rear), PS/2 Mouse & Keyboard

TVNP Protocol - Issue 3

TVNP Protocols Implemented - Layer 1 (Full: RS232 and UDP/IP), Layer 2 (Full),

Layer 3 (Full, excluding confidence indicators), Layer 4 Video Routing Protocol (VRP-1) (Full),

Layer 4 Camera Control Protocol (CCP-1) (Full, as applicable to ZoneVu system), Layer 4

Network Management Protocol (NMP-2 v2.0) (Partial)

TVNP Data Connections - 6 (Direct), Unlimited (Indirect)



The purpose of this data sheet is to provide product information on Meyertech products. The information in this datasheet is believed to be accurate and reliable. However, no responsibility or liability is assumed by Meyertech Limited for its use, or for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or other rights of Meyertech Limited. Meyertech are committed to continuous product development and therefore reserve the right to change specification without notice.

