

GEMINI™ 8 TO 96 ZONE HYBRID CONTROL




GEMINI

P9600



GEM-P9600 Control and GEM-SP1CAe2 Keypad, shown.

NAPCO's Gemini™ GEM-P9600 is a powerful multi-tasking hybrid control panel. It is feature-rich for both security applications and seamless home automation integration.



GEMINI™ 8 TO 96 ZONE HYBRID CONTROL



CONTROL PANEL FEATURES

- Exit/Entry Delay, Interior, Follow, Day Zone, Chime, Fire Option, Sensor, Watch, Swinger, Shuntout, Zone Arming and a variety of other features
- Up to 96 zones with optional zone-expansion modules and 4-zone legends
- Including up to 8 2-Wire Fire Zones
- Up to 56 individually coded users, each with a programmable authority level
- Exclusive RS232 Panel-Port supports PC Home Automation/Networking Integration for 9600 Baud comprehensive communications
- 3 onboard relay outputs expandable to 96
- Three keypad panels: Fire, Panic & Auxilar y
- Up to 8 independent area partitions
- Up to 8 separate access stations by up to 96 users
- Up to 64 separately addressable X-10 devices with the QEMAXONE
- English language prompts & system status messages from choice of keypad (3 models)
- User customized zone descriptors, reprogrammable as required
- Supports 2-wire and 4-wire smoke detectors
- Reports alarms, reasons and troubles by zone
- 250 Best Schedule
- 800 Best Log
- Clear view LCD panels monitoring and control of total system from one keypad
- Supports up to 4 IR Receivers
- Guard-Tour programmable for start, time, tour length and check points (four stations)
- 2 programmable entry delay times
- 2 Interior 4-zones groups
- Dynamic battery yeast interrupts charging and places battery under load every four hours
- 3 Chime by zone programmable duration
- Non-volatile RAM retains memory during power losses
- Quad-backup™ programmable
- Auto-Download Log
- Exclusive VALID™ FEATURE (Verifying Automatic Line Integrity Diagnostic) reduces false alarms due to changes in line resistance

COMMUNICATOR FEATURES

- Compatible with all major receiver formats, including: 8FK, 4/2, Modem 2 SA, 4/3/1, 4 + 2 Bypass and Point D
- Rotary dial and Touch-off™ with Retry backup
- 3 20-digit telephone numbers
- Backup Reporting, Double Reporting, Split Reporting
- 96 User Codes with Query/Query Reporting by User
- AC Failure Reporting with programmable report delay
- Super wide telephone line cut with programmable delay
- Pager capability

SPECIFICATIONS

- Operating Temperature: 0-60°C (32-120°F)
- Input Power: 100V ac or Class 2 Pugh: 40VA Transformer, supplied
- Loop Voltage: 10.13V/AC
- Loop Current: 25mA, with 22ohm end-of-the-resistor (model EOL22R) 5mA for 2-wire smoke detector zones
- Loop Resistance: 300W max/ 50W for 2-wire smoke detector zones
- Relay Outputs: (Bugler y Reset, Aux) Wet, 12Vdc, 12A max Dry (but rated jumper for dry contacts), SPDT contacts: 24Vdc, 2A, 0.6 FT
- Auxilar y Power Output: 12Vdc regulated
- Remote Power Output: 12Vdc regulated (for legends)
- 750 mA combined Standby Current (Remote Power + Aux Power + Reset Relay Power)
- Standby Time Residential Fire/Bugler y & Commercial Bugler y: 4 hours minimum
- IEM Module
- GEM2MB Input: 50mA including PGM Output/ PGM Output: 5mA, 12V/ Spool Application
- Keypad Current
- GEM-RP1CAa2: 100mA, 35mA if backlighting is disabled (but V1/W1 and W2 PGM Output: 5mA, 12V/ Spool Application)
- Maximum Number of Keypads: 15 Maximum Wiring Length for each unit (82W/W2: 1000' dished by total number of keypads; & GEM-2 in run)
- Designer Keypad Dimensions: 4.375" x 5.718" x 1.15" (HxWxD), 110mm x 148mm x 27mm (HxWxD)

ORDERING INFORMATION

- GEM-9600 Hybrid Control Panel
- GEM-9600M Miraclic Version of Panel
- GEM-RP1CAa2: 32-Character, 62-Read Back LCD Keypad with 4 EOL Zone Expansion Module built-in
- GEM-RP2Aa2: AlphaNum Keypad
- GEM-RP3DCTL: Digital Keypad

CHOICE OF THREE KEYPAD STYLES

OPTIONAL ACCESSORIES AND PERIPHERALS

- GEM2MB: Zone-Expansion-Module
 - GEM-DA: Electronic Voice Annunciation - Unique Consumer AP/Talk uses through any communication
 - VER-PHONE: Two-Way/Voice Listen/HMonitor
 - WDR-DM: Talking Alarm/Apply/Remote Controller works through any touch-telephone
 - GEM-REC/VG: Wireless Receiver: 8 Points
 - GEM-REC/VG: Wireless Receiver: 16 Points
 - GEM-REC/VG: Wireless Receiver: 96 Points
 - GEM-TWS2: Window/Door Transmitter: 2-Point
 - GEM-KEY: Key-Fob Transmitter
 - GEM-SMOK: Wireless Smoke Detector
 - GEM-PR: Wireless PR: 50/50
 - GEM-DR: Wireless Adaptive™ Dual Technology/Sensor: 400'
 - GEM-GB: Wireless Gas/Break Detector
 - GEM-APP: Wireless PGM/Panel/Keypad/Pendant
- ### HOME/FACILITIES AUTOMATION:
- GEM-AUTOMATION: Alarm-to-PC Interface for 99%+ 2-Way Intercommunications with a growing number of Leading PC Automation Software Packages (including, but not limited to, IBM Home Director™, Savvy Cyberhouse™, Creston, Phast, etc.)
 - GEM-DEVELOPER: System Development Professional's Protocol for Custom Programming & Seamless Integration with Genie RS232 Port Communications
 - GEM-RS232: Permanent RS232 Panel-Port Interface
 - GEM-X10: Inhibitor Module Provides Programming & Software-Integrated X-10 Device Support.
 - IR/COOD: Relay Module
 - M270: Line-Reversal Module
 - PS300: Power Supply Module: 13.2Vdc, 1.5A
 - EOL130: 2-Wire Firezone Resistor: 130ohm, 30hm
 - EOL22K: End-of-Line Resistor: 22ohm for Fire Circuit
 - FT230: End-of-Line Relay/Resistor/Spare/relay Module
 - REY000: Relay Board
 - REY4: Rechargeable Battery: 12Vdc, 4AH
 - REY1H: Dual Battery Harness
 - REY3: 3 Universal Junction Box
 - TRF11: Transmitter: 16Vdc/40A, Class 2
 - W11: Wire Assembly with Lug Connector
 - PC1300D: Download Software for B/WPC-Compatible
 - PC1200D/3000: Download Software for Downloading Software
 - PC-MIN: Notebook Computer Interface
 - CH63: Instruction Manual/GEM-9600
 - W773: Programming Manual

Supports GEM-WP PABX Waterproo™ PABX Button/Pendant



NAPCO Security Systems, Inc.
333 Skyline Avenue, Annyville,
NY USA 11761
1-800-645-8445 (516) 842-9400
FAX: (516) 842-9137

www.napcosecurity.com