
CRC101 - CARD READER CONTROLLER

The CRC101 is a stand alone access control unit designed for indoor use, that supports a single magnetic stripe or proximity card reader. The unit is programmed using on board buttons with feedback from a 4 digit display. This single reader controller gives a voltage free relay contact output.











ASC121T

Features

- Stand alone control unit
- Built in CRC100 controller
- Capacity 10,000 cards with site code
- Validate/void individual cards
- Validate/void groups of cards
- Card status verification
- Variable output relay timing (0 – 30 secs)
- Anti-time back (0-30 secs)
- Push button programming
- Supports magnetic stripe and proximity readers
- Built in power supply
- Free exit or arming facility
- 4 digit LED Display
- Voltage free relay contact
- Lockable indoor housing
- Ability to parallel 2 readers for single door entry/exit control

Options

Battery back up

Applications


- Door access control
- Turnstiles and automatic gate control





SPECIFICATIONS

Typical configuration for the CRC101



CRC101

Supply voltage	220V AC *0.75 Amp 12V available supply for lock with battery back-up capacity
Size	245 x 195 x 85mm
Output	Voltage free change over relay rated at 30V DC @ 2A
Cabling	CRC101 to card reader, Belden Cable 9536 (50m Max)
Unit weight	2.7kg

RH301 Magnetic stripe card reader

•	•
Supply voltage	4.5V – 6.4V (supplied by CRC100)
Operating temp	-40°c to +75°c
Current Draw	20mA
Read head life	300,000 swipes
Housing	Aluminium die cast
Electronics	Conformally coated
Unit size	50 x 33 x 140mm
LED Indicator	Bi-colour

ASR603 Slim proximity card reader

•	<u> </u>
Supply voltage	5.0V – 14V DC (supplied by CRC100)
Operating temp	-30°c to +65°c
Read range	Up to 12.7cm
Housing	Single-piece construction with potted electronics
Electronics	Fully potted
Unit size	114 x 44 x 22mm

Ordering Information

CRC101	Card reader control unit
RH301	Magnetic stripe card reader
CC420-HCN	Magnetic stripe cards
ASR603	Slim proximity card reader
ASR610	Mid range proximity reader
ASC121T	Standard proximity cards

Supplied by:



