



Outdoor Mesh Access Point (AP-4900MR-LR)



Indoor Mesh Access Point (AP-4900M)

## Outdoor Broadband Wireless Access

Proxim Wireless offers the industry's most complete suite of outdoor broadband wireless access products. This portfolio includes:

- **Tsunami™ MP.11** – Capabilities of fixed and mobile WiMAX for U.S. and global markets
- **Tsunami™ MP.16** – WiMAX for the 3.5 GHz frequency band
- **ORiNOCO® Wi-Fi Mesh** – Outdoor and indoor Wi-Fi mesh for service providers and municipalities

**Proxim Wireless** is a global pioneer in scalable broadband wireless networking. From Wi-Fi to wireless Gigabit Ethernet – our WLAN, mesh, point-to-multipoint and point-to-point products are available through our extensive global channel network.

## High Capacity Mesh Access Points Deliver Flexible, Scalable, and Reliable Data, Voice and Video for Large Public Safety and Wi-Fi Deployments

Supporting both 4.9 GHz public safety and 2.4 GHz metropolitan Wi-Fi networks through dual 4.9/2.4 GHz radios, ORiNOCO Public Safety Wi-Fi Mesh delivers the versatility and feature robustness required by today's demanding emergency response and metro Wi-Fi applications. Delivering unparalleled enterprise-scale security, management and Quality of Service (QoS) features, the access points are preconfigured with tri-mode support for best in class performance and flexibility in large public safety deployments. Offering a cost-effective, scalable mesh solution, ORiNOCO Public Safety Wi-Fi Mesh Series consists of indoor and outdoor form factors. The AP-4900M indoor access point's small form factor enables installation in a building or a vehicle trunk. Housed in a ruggedized enclosure, the AP-4900MR-LR<sup>1</sup> may be deployed outdoors in extreme weather conditions.

- The ORiNOCO Mesh Creation Protocol (OMCP) enables mesh backhaul and Wi-Fi coverage on one radio, while the second radio is used exclusively for Wi-Fi coverage
- Industry-leading throughput with 802.11g and 4.9 GHz simultaneous operation
- Robust RADIUS accounting and authorization interface enables detailed subscriber usage tracking
- WMM/802.11e draft Quality of Service support for data, voice, and video

## Proactive Security Measures to Protect Your Network

ORiNOCO access points support the latest security standards, including IEEE 802.11i and AES encryption, and add proactive security measures to prevent attacks.

- Intra-cell blocking and traffic redirection to prevent subscriber-to-subscriber attacks
- Broadcast bandwidth throttling prevents broadcast attacks
- IEEE 802.1x mutual authentication
- Dynamic per-user, per-session rotating keys
- Rogue access point detection and notification
- Secure management interfaces: SNMPv3, SSL and SSH

## Easy to Deploy and Manage

Ease of deployment and integration with the wired network are critical factors in a successful, profitable wireless network rollout. ORiNOCO access points excel with key capabilities that simplify WLAN deployment.

- Self-forming and self-healing ORiNOCO Mesh Creation Protocol automatically routes traffic through the best path as mesh access points are added or removed from the network
- Tools to speed installation and optimization: automatic channel selection, adjustable transmit power, external antenna connectors<sup>2</sup>
- Remote management via SNMP, HTTP and Telnet

## Reliable by Design

With over 25 years of experience in the design and manufacture of wireless LANs, Proxim Wireless understands that service providers and enterprises require the same uptime and reliability in a wireless network as in a wired network. ORiNOCO access points offer:

- Robust features for metropolitan Wi-Fi and enterprise applications
- Automatic reconfiguration of security policy in the event of power loss
- Dual firmware image support – for rollback in the event of software or configuration change problems
- Power-over-Ethernet support
- AC Power option for light pole installations<sup>3</sup>

<sup>1</sup>Available for FCC only.

<sup>2</sup>External antenna connectors not available on all indoor models.

<sup>3</sup>Available for AP-4900MR-LR version only.

## APPLICATIONS

- Emergency Services**  
 Real-time computer-aided-dispatch on the move. Mobile office, voice, live-streaming video, and data connectivity for first responder vehicles.
- Metro Wi-Fi & 4.9 GHz Public Safety**  
 Simultaneous 4.9 GHz Public Safety access and 2.4 GHz Metro Wi-Fi coverage on a single, dual-radio platform.

## PERFORMANCE AND SCALABILITY

ORINOCO Mesh Creation Protocol (OMCP)	Self-forming/self-healing dual-radio wireless mesh backhaul for industry leading throughput and availability
Tri-mode 802.11b, 802.11g and 4.9 GHz Support	Pre-configured, simultaneous 802.11b, 802.11g, 4.9 GHz support
Field Upgradeable	Software upgradeable to support new standards
IEEE 802.11i and AES Encryption	Highest authentication and encryption methods including mutual authentication, message integrity check (MIC), per-packet keys initialization vector hashing and broadcast key rotation
Rogue AP and Client Detection	Detects and alerts unauthorized rogue Access Points and clients in both the 2.4 and 4.9 GHz bands
Secure Management Interfaces	SNMPv3, SSL and SSH protect against unauthorized AP changes via the management interface
Multiple VLAN Support with Different Security Settings	Up to 16 separate VLANs per radio each able to support different authentication and encryption algorithms simultaneously
Multiple BSSID Support	Up to 4 Basic Service Set identifiers (BSSIDs) per radio
Auto Configuration via DHCP	Ensures new APs automatically receive correct configuration and prevents security vulnerabilities with deliberate resets
Assured Software Upgrades	Guarantees new AP configuration file is valid before deleting current image - dual image support
Quality of Service (QoS)	Draft IEEE 802.11e along with 802.1p and 802.1q improve performance of video and voice applications
Transmit Power Control	Supports selectable transmit power levels to adjust coverage cell size
Automatic Channel Selection	Simplifies installation by choosing best possible channel upon installation
RADIUS Support	Extensive RADIUS Authentication Accounting support
Super Mode	Delivers greater than 30 Mbps throughput for ORINOCO and Atheros-based clients while simultaneously compatible with non-Atheros clients
Advanced Filtering Capabilities	IEEE 802.1d bridging with static MAC address filtering, network protocol filtering, Proxy ARP, multicast/broadcast storm threshold filtering, TCP/UDP port filtering, intra-cell traffic filtering to prevent client-to-client snooping
Near Line of Sight Capable	Line of sight and near line of sight connectivity extends deployment flexibility in rural as well as high-density urban areas

# ORINOCO Public Safety Wi-Fi Mesh Technical Specifications

	ORINOCO AP-4900M*	ORINOCO AP-4900MR-LR <sup>1</sup>
<b>PRODUCT MODELS</b>	8670M-PS-US ORINOCO AP-4900M Tri-mode, Mesh Access Point	8670-MR-LR-PS-US ORINOCO AP-4900MR-LR Tri-mode, Outdoor Mesh Access Point
<b>RADIO &amp; TRANSMISSION</b>		
<b>MODULATION METHOD</b>		
802.11B OR G	OFDM; DSSS	OFDM; DSSS
802.11A	OFDM	OFDM
<b>FREQUENCY BAND</b>		
802.11B/G	2.412 to 2.462 GHz	2.412 to 2.462 GHz
802.11A	5.25 to 5.35 GHz (FCC UNII 1 and UNII 2), 5.725 to 5.85 GHz (FCC UNII 3 ISM)	N/A
4.9 GHz	4.94 to 4.99 GHz (FCC Only)	4.94 to 4.99 GHz (FCC Only)
<b>DATA RATE</b>		
4.9 GHz 10 MHz CHANNELS	3, 4.5, 6, 9, 12, 18, 24, 27 Mbps	3, 4.5, 6, 9, 12, 18, 24, 27 Mbps
4.9 GHz 20 MHz CHANNELS	6, 9, 12, 18, 24, 36, 48, 54 Mbps	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11B	1, 2, 5.5, 11 Mbps	1, 2, 5.5, 11 Mbps
802.11G	6, 9, 12, 18, 24, 36, 48, 54 Mbps	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11A	6, 9, 12, 18, 24, 36, 48, 54 Mbps	N/A
<b>MAX OUTPUT POWER</b>	+18 dBm for 802.11g and 802.11a/4.9 GHz; +20 dBm for 802.11b	+20 dBm for all modulations on 4.9 GHz; +24 dBm for 802.11b/g
<b>INTERFACES</b>		
<b>WIRED ETHERNET</b>	10/100Base-T Ethernet (RJ-45)	10/100Base-T Ethernet (RJ-45)
<b>WIRELESS</b>	1 integrated 802.11b/g radio and 1 integrated 802.11a radio	1 integrated 802.11b/g radio and 1 integrated 4.9 GHz radio
<b>ANTENNA CONNECTOR</b>	Integrated diversity 2.4 and 4.9/5 GHz antennas with horizontal and vertical polarization and external antenna connectors 802.11 b/g and 802.11a/4.9 GHz	Two external Type-N Female connectors; one connector for a 2.4 GHz antenna and one connector for a 4.9 GHz antenna
<b>PHYSICAL</b>		
<b>DIMENSIONS</b>		
PACKAGED	11.375 x 9.25 x 2.75 in (288.9 x 235 x 69.9 mm)	14.57 x 13.7 x 8.19 in (370.1 x 348 x 208 mm)
UNPACKAGED	7.8 X 4.75 X 1 in (198 x 121 x 25 mm)	10.5 x 10.5 x 3.25 in (267 x 267 x 83 mm)
<b>WEIGHT</b>		
PACKAGED	2.05 lbs (0.93 kg)	11.1 lbs (5.03 kg)
UNPACKAGED	0.65 lbs (0.29 kg)	5.5 lbs (2.49 kg)
<b>ENVIRONMENTAL</b>		
<b>TEMPERATURE</b>	0° to 55°C (Operating) -20° to 85°C (Storage)	-35° to 60°C (Operating) -55° to 80°C (Storage)
<b>HUMIDITY</b>	Max 95% relative humidity (non-condensing)	Max 100% relative humidity (non-condensing)
<b>WIND LOADING</b>	N/A	125 mph
<b>WATER &amp; DUST PROOF</b>	N/A	IP65
<b>ELECTRICAL</b>		
<b>POWER SUPPLY</b>	AC: 110/240 VAC, 50/60 Hz (input); 5V 3A (output)	PoE: 110/240 VAC (input); 48 VDC ± 10% (output)
<b>(OPT) POWER SUPPLY</b>	IEEE 802.3af Active Ethernet Support (purchased separately)	110/240 VAC light pole power tap (purchased separately)
<b>POWER CONSUMPTION</b>	Maximum 10 Watts	Maximum 20 Watts
<b>LEDS</b>	Power, Ethernet LAN Activity, Wireless B/G Activity, Wireless 802.11a Activity	Power/Ethernet LAN Link, Wireless LinkMax
<b>MANAGEMENT</b>		
<b>LOCAL</b>	RS-232 Serial Port; DB9 Female	RS-232 Serial Port; RJ11 Female
<b>REMOTE</b>	DHCP, Telnet, HTTP, TFTP, Boot P, SNMPv1/v2c/v3; ORINOCO MIB, Etherlike MIB, 802.11 MIB, Bridge MIB, MIB-II	DHCP, Telnet, HTTP, TFTP, Boot P, SNMPv1/v2c/v3; ORINOCO MIB, Etherlike MIB, 802.11 MIB, Bridge MIB, MIB-II
<b>SECURE</b>	SNMPv3, SSH, HTTPS	SNMPv3, SSH, HTTPS
<b>MTBF AND WARRANTY</b>	100,000 hours; 1-year on parts and labor	100,000 hours; 1-year on parts and labor
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"> <li>(1) AP-4900M tri-mode access point</li> <li>(1) AC Power adapter and support for Active Ethernet and IEEE 802.3af (AE injector purchased separately)</li> <li>(1) Cable cover and Ceiling/Wall mounting Plate</li> <li>(1) Installation CD-R</li> </ul>	<ul style="list-style-type: none"> <li>(1) AP-4900MR-LR dual-radio mesh access point</li> <li>(1) Power injector and power cord</li> <li>(1) RJ11 to DB9 serial connector</li> <li>(1) Cable termination kit</li> <li>(1) Wall/Pole Mounting bracket and hardware</li> <li>(1) Installation CD-R</li> </ul>
<b>RELATED PRODUCTS</b>	ORINOCO AP-4900MR-LR, AP-4000MR and AP-4000MR-LR to extend mesh network outdoors, 2.4 GHz antennas, 4.9 GHz antennas, ProximVision Network Management System, Tsunami MP.11 for backhaul between groups of mesh radios, ServPack (US/CAN Only)	ORINOCO AP-4000MR-LR 2.4/5.8 GHz mesh access points, 2.4 GHz Direct Connect Antennas (1086-OA24-DC5 & 1086-OA24-DC8), 4.9 GHz Direct Connect Antenna (1086-OA52-DC8), AC Power Kit for lightpole mounted AP (1089-AC-KIT-TW), Wide Light Pole Mounting Kit (1090-LP-MINT-WD), ProximVision™ NMS, Tsunami MP.11 for backhaul between groups of mesh radios, ServPak for Enhanced Support (US/CAN only)

<sup>1</sup>Available for FCC only.

For detailed technical specifications, please go to <http://www.proxim.com/products/wifi/ap/>

©2006 Proxim Wireless Corporation. All rights reserved. Proxim is a registered trademark and the Proxim logo and ORINOCO are trademarks of Proxim Wireless Corporation. All other trademarks mentioned herein are property of their respective owners. Specifications are subject to change without notice.

DS\_0806\_ORAP4900\_US



Proxim Wireless Corporation  
[www.proxim.com](http://www.proxim.com)