

L50DC4P

50mm F1.8 - CS-Mount

Compatible with 1/3" & 1/4" Cameras

Focal Length: 50mm

Max. Relative Aperture: 1:1.8

Iris: F1.8~Approx. F360

With ND Spot Filter

Angular Field of View: 1/3": $5.5^{\circ} \times 4.1^{\circ}$

1/4": $4.1^{\circ} \times 3.1^{\circ}$

Min. Object Distance

(M.O.D.):

0.7m (From Front Vertex)

Optical Back Focal

Distance:

19.71mm (In Air)

Operation: Focus: Manual

Iris:

IG (Auto-Close System)

Operation Voltage: Close to Open: Less than 3V

Open to Close: More than 0.5V

Operation Temperature: $-10 \sim +50^{\circ}\text{C} \ (+14 \sim 122^{\circ} \text{ F})$

Filter Size: 43mm P0.75


Mount: CS-Mount


(Adjustable Lens Postion)

Size, Approx. Weight: $50.9 \times 60 \times 44.2$ mm (w/h/d), 125g

75mm

(Approx. $2.0 \times 2.4 \times 1.7$ in., 4.4oz.)





L75DC4P

Focal Length:

75mm F1.8 – CS-Mount

Compatible with 1/3" & 1/4" Cameras

Max. Relative Aperture: 1:1.8

Iris: F1.8~Approx. F360

With ND Spot Filter

Angular Field of View: 1/3": $3.7^{\circ} \times 2.8^{\circ}$

1/4": $2.8^{\circ} \times 2.1^{\circ}$

Min. Object Distance

(M.O.D.):

0.8m (From Front Vertex)

Optical Back Focal

Distance:

21.85mm (In Air)

Operation: Focus:

Iris:

Manual IG (Auto-Close System)

Operation Voltage:

Close to Open: Less than 3V Open to Close: More than 0.5V

Operation Temperature: $-10 \sim +50^{\circ}\text{C} \text{ (+14} \sim 122^{\circ} \text{ F)}$


Filter Size: 46mm P0.75

Mount: CS-Mount

(Adjustable Lens Postion)

Size, Approx. Weight: $50.9 \times 60 \times 63.5$ mm (w/h/d), 200g

(Approx. $2.0 \times 2.4 \times 2.5$ in., 7.1oz.)



Camera Connector Wiring		
1 3	Pin	Signal
	1	Brake – *
	2	Brake + *
	3	Drive +
2 4	4	Drive –
* Also referred to as DAMP, CONTROL, or DUMP		