

Designed for Access Control



Harmony Series
Online Integrated Wiegand
Access Control Solution







Sophisticated Wiegand solution.

Big features in a small, well-styled lock. Card reader, monitoring capabilities and SARGENT ANSI/BHMA Grade 1 hardware with direct Wiegand output are beautifully presented in the Harmony Series. Designed to blend into any environment flawlessly, Harmony is in tune with the aesthetic needs of the architect, and provides high security for the facility manager. With all components consolidated into the lock, installation time is reduced significantly compared to traditional access control installations.



Features

- Integrated ANSI/BHMA Grade 1 hardware, available in
 - 10 Line Bored Lock
 - 8200 Series Mortise Lock
 - 80 Series Exit Device
- Supports HID® 125 kHz prox or 13.56 MHz iCLASS® credentials
- Consolidates all components into the lock
 - Card reader, door position switch and request to exit monitoring sensors
 - Eliminates reader interface modules
 - Lockdown capable
- Secure-side electronics
- For use on exterior doors: weatherseal gasket standard; shroud available
- Available with MicroShield® antimicrobial finish
- Provided with plug and play ElectroLynx® connectors for ease of installation

Available with SARGENT Designer Levers

- Studio Collection
- Coastal Series





ASSA ABLOY Group brands are the only providers of a complete range of access control solutions with full iCLASS® authentication.

MicroShield®



As part of their promise to provide innovative solutions to their customers, certain ASSA ABLOY Group brands offer the MicroShield® technology, a silver-based antimicrobial coating designed to inhibit the growth of bacteria.

MicroShield® is a registered trademark of Yale Security Inc., an ASSA ABLOY Group company.

ElectroLynx®



As part of their promise to provide innovative, fast and effective high security solutions to their customers, certain ASSA ABLOY Group brands offer ElectroLynx $^{\otimes}$, a universal quick-connect system that simplifies the electrification of the door opening. ElectroLynx $^{\otimes}$ is a registered trademark of ASSA ABLOY Inc.

SARGENT Manufacturing Company For more information call 800-727-5477 or visit us online at www.sargentlock.com

Copyright © 2009, 2010 Sargent Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Sargent Manufacturing Company is prohibited.


HID and iCLASS are registered trademarks of HID Global in the U.S. and/or other countries. The Genuine HID Technology logo is a trademark owned and licensed by HID Global.

Benefits

- Open architecture platform compatible with all popular access control systems
- Reduces installation time dramatically
 - Requires only one cable run from the lock to the access control panel
 - Maintains architectural integrity around the door
 - Fewer discrete components to install than traditional access control
- Direct Wiegand output eliminates need for interface panel
- No special credentials needed; works with your facility's prox and iCLASS cards
- Fewer terminations result in improved reliability

Specifications and System Requirements

- 125 kHz prox: reader 12VDC; lock available as 12 or 24VDC
- 13.56 MHz iCLASS: lock and reader available as either 12 or 24VDC
- Fail Safe and Fail Secure solenoid versions available
- Listed to UL 294 (Access Control System Units). UL 294 is a U.S. only system level certification. For information regarding access control system compliance, please call 800-810-WIRE.



* U.S. Patent D601,001S; D601,002S; D601,003S; D602,762S





