

Leading the way in security

Scantronic

9448+ STYLE HARD WIRED ALARM SYSTEM

CONTROL PANELS



The 9448+ is an ideal choice for either residential or small commercial installations, designed specifically to offer exceptional value for money.

The aesthetically appealing and yet robust white outer case, LED display and soft tactile illuminated keypad all combine to give an attractive look to the product, designed to blend in with your décor.

Scantronic have designed the 9448+ to meet the most professional alarm installation standards and yet have made the product easy to install, using simple but secure wiring.

The control panel has up to 7 zones of protection, day LED, 10 event log, 2 communication outputs (for speech dialler) and a programmable fire zone. A global anti-tamper zone has been incorporated with provision for 3 outputs, bell, strobe, PIR set latch or shock sensor reset.

Easy to operate, this system has full and part set facilities, the ability to change access codes and 2 remote keypads, to give you a high level of security benefits and total peace of mind.

9448+ STYLE HARD WIRED ALARM SYSTEM

TECHNICAL SPECIFICATION

Zones	7 closed circuit (zone 7 pre-programmed as entry/exit)
Zone Attributes	Personal attack, normal alarm, chime, omit, not used, part set omit, fire, entry route
Panel	9448UK-90 = control panel with on-board tactile illuminated rubber keypad
Keypads	Accepts up to 2 remote 9427 Style keypads. Dual key personal attack (PA)
Display	10 LED (Light Emitting Diode) indicators on control panel, inc. day (unset) LED
Anti-Tamper Circuits	Global
Event Log	10 events recorded
Expansion	No
Full/Part Set	Fully programmable part set option
Compliance	BS 4737
Panel Siren	Yes
Internal Sounder	Accepts 1 x 16 ohm internal sounder
Outputs	Bell and strobe 500mA open collector. 1 programmable 100mA as PIR set latch and/or shock sensor reset
Bell Duration	Programmable up to 20 minutes
Entry/Exit Times	5 programmable entry and exit times
Battery	2.1 Ah lead acid gel type rechargeable.
12V Power	Quiescent - Panel = 55mA. Keypad = 20mA
Aux DC Power	500mA @ 13.8v
Dimensions	Control panel (H x W x D) = 212 x 212 x 68mm. Keypad (H x W x D) = 115 x 115 x 28mm
Weight	Control panel 1.2kg
Temperature Range	-10°C to +55°C
Communication Output	Personal attack (PA) and burg (for speech diallers only)
Compatibles	Control panel operates with all types of detectors, bells and sirens
Scantronic Compatible Equipment	9427 Remote Keypad 9040 16 ohm Internal Siren 660 Speech Communicator 420 PIR Detector 460 Twintec Detector

Scantronic is a leading brand of Cooper Security Ltd, part of Cooper Industries, employing over 28,000 people in 100 manufacturing sites around the world.

Scantronic manufactures security equipment for all types of commercial and domestic premises. The range is comprehensive, offering every type of solution from multizone hard-wired and wirefree systems, to digital and voice communicators, to detectors and social alarms. Installers trust us to deliver cost effective products with the highest quality of field and support services to ensure you receive the best and most reliable systems to secure you and your premises.

Dealer Details