## 660 SPEECH DIGITAL COMMUNICATOR

security

eading the way in



The 660 is a wire-in auto dialling speech/digital communicator unit, designed to be discreetly fitted in a Scantronic, or any other manufacturer's alarm control panel.

Should you wish to have your premises monitored by family, friends, neighbours, company members or a remote monitoring centre, the 660 offers a wide variety of choices, tailored to suit your specific budgetary and installation requirements.

The Speech Communicator option is programmed via a DTMF touch-tone telephone and is capable of sending 4 pre-recorded voice messages to family, friends, neighbours, company members' etc over the telephone line. The voice message has one, eight-second master message, normally used to record your name and address and up to four, three-second secondary messages. These are normally used to indicate the type of incident e.g. personal attack, burglary, fire etc.

The Digital Communicator option is programmed via a DTMF touch-tone telephone using the advanced programming function. This will allow the communicator to be received in Scancom Fast Format Remote Monitoring Centres.

The Scantronic 660 offers a wide variety of choices should you wish to have your premises monitored, providing enhanced security to your alarm system, giving you total peace of mind.







## 660 SPEECH DIGITAL COMMUNICATOR

## TECHNICAL SPECIFICATION

Stand Alone Unit
Two Levels of Programming

DTMF Programming
Number of Voice Messages

Number of Telephone
Messages
Security Code
Communicates to a Remote
Monitoring Centre
Telephone Line Connection
Weight
Dimensions (H x W x D)
Power Supply
Outputs
Temperature

**Approvals** 

Wire-in unit designed to be used with any alarm control panel

Programmed as a speech communicator, digital communicator, or both. With two levels of programming, basic and advanced

Programmed via a DTMF telephone with complete Non Volatile Memory (NVM) backup Delivers up to 4 programmed voice messages (one eight second master message, and up to four three-second secondary messages)

 $Calls \ up \ to \ four \ telephone \ numbers \ in \ sequence, \ until \ acknowledged \ or \ until \ 15 \ attempts \ are \ made$ 

A security code can be programmed to prevent unauthorised changes to the programmed information If programmed the 660 will communicate to any alarm receiving equipment that uses Scancom Fast Format

Direct exchange lines (PSTN) supporting DTMF (tone) or Loop Disconnect (pulse) dialling 110 grams

85 x 120 x 26mm

10mA quiescent (12v ± 3v dc) - 75Ma

Remote or locally controlled. Open collector, 100Ma active

-10°C to +55°C

BABT approved

Scantronic is a leading brand of Cooper Security Ltd, part of Cooper Industries, employing over 28,000 people in 100 manufacturing sites around the world.

Scantronic manufactures security equipment for all types of commercial and domestic premises. The range is comprehensive, offering every type of solution from multizone hard-wired and wirefree systems, to digital and voice communicators, to detectors and social alarms. Installers trust us to deliver cost effective products with the highest quality of field and support services to ensure you receive the best and most reliable systems to secure you and your premises.

Dealer Details



