



# MIFARE® credentials



## Overview

Schlage® offers a variety of MIFARE® credential technology options to fit the needs and budget of most every application. All MIFARE credentials from Schlage are encrypted and secure, but also based on open, global standards, ensuring a future of headache-free flexibility and scalability. Schlage MIFARE credentials offer a single credential solution for secure physical and logical access and are available in a variety of form factors to fit any facility or business need, including ISO style cards, clamshell cards, wristbands, key fobs and adhesive patches. All Schlage MIFARE credentials are compliant with international standard ISO 14443. Schlage 13.56 MHz contactless MIFARE credentials are offered with the following industry standard technologies:

#### MIFARE Classic®

Schlage credentials using MIFARE Classic® technology are ideal for facilities with moderate security needs, and for businesses that want to use credentials to support multiple business functions.

- Simple, fixed memory structure
- Freely programmable memory
- Multiple memory options and form factors

#### MIFARE® DESFire®

MIFARE® DESFire® delivers the perfect balance of security, speed and performance. Its open protocol design allows future seamless integration of other applications.

- Flexible file system/flexible memory organization
- Fast and secure data transmission
- 128 AES encryption used for authenticity, confidentiality and integrity
- Multiple memory options and form factors

# Features and benefits

- Open architecture design is built on ISO 14443A standards, providing for a faster data transfer speed
- Offered in clamshell, ISO style cards, keyfobs, wristbands and adhesive patches
- Utilizes MIFARE Classic or MIFARE DESFire
- Custom artwork and laser engraving available for clamshell and ISO style cards





Scan or click the link below to check out our Schlage Credential Services

## 13.56 MHz MIFARE credentials













Model number	8420, 8440, 8480	8520, 8540, 8580	8720, 8740, 8780	2420, 2440, 2480	2520, 2540, 2580	2620T
Credential type	Clamshell	ISO glossy white <sup>1</sup>	PVC adhesive patch	Clamshell	ISO glossy white <sup>1</sup>	Thin keyfob
Credential technology; ISO standard	MIFARE DESFire EV14	MIFARE DESFire EV14	MIFARE DESFire EV14	MIFARE DESFire EV24	MIFARE DESFire EV24	MIFARE DESFire EV2
Magnetic stripe	No	Yes <sup>2</sup>	No	No	Yes <sup>2</sup>	No
Dimensions (H x W x T)	3.37" x 2.125" x 0.075"	3.37" x 2.125" x 0.033"	3.37" x 2.125" x 0.033"	3.37" x 2.125" x 0.075"	3.37" x 2.125" x 0.033"	2" x 1.24" x 0.38"
Slot punch³ (printed guide included on ISO cards)	Vertical (standard)	Vertical or horizontal (optional)	Vertical or horizontal (optional)	Vertical (standard)	Vertical or horizontal (optional)	Keyring
Memory capacity; application sectors	2K byte/16k bit 4K byte/32k bit 8K byte/64k bit	2K byte/16k bit				

## 13.56 MHz MIFARE credentials













Model number	9420, 9451	9520, 9551, 9558	9651	9651T	9351	9751, 9758
Credential type	Clamshell	ISO glossy white <sup>1</sup>	Keyfob	Thin keyfob	Silicone wristband	PVC adhesive patch
Credential technology; ISO standard	MIFARE Classic <sup>4</sup>	MIFARE Classic <sup>4</sup>	MIFARE Classic <sup>4</sup>	MIFARE Classic <sup>4</sup>	MIFARE Classic <sup>4</sup>	MIFARE Classic <sup>4</sup>
Magnetic stripe	No	Yes <sup>2</sup>	No	No	No	No
Dimensions (H x W x T)	3.37" x 2.125" x 0.075"	3.37" x 2.125" x 0.033"	2" x 1.24" x 0.38"	1.77" x 1.18" x .06"	0.63" x 7.68" x 0.295"	3.37" x 2.125" x 0.033"
Slot punch³ (printed guide included on ISO cards)	Vertical (standard)	Vertical or horizontal (optional)	Keyring	Keyring	N/A	Vertical (optional)
Memory capacity; application sectors	2.5k bit; 5 sectors 1K byte/8k bit; 16 sectors	2.5k bit; 5 sectors 1K byte/8k bit; 16 sectors 4K byte/32k bit: 40 sectors	1K byte/8k bit; 16 sectors	1K byte/8k bit; 16 sectors	1K byte/8k bit; 16 sectors	1K byte/8k bit; 16 sectors 4K byte/32k bit; 40 sectors

Limited lifetime warranty - Credentials have a lifetime warranty against manufacturers defects. See sales policy for complete warranty details.

<sup>4</sup> All Schlage MIFARE credentials comply with the 14443 ISO standard.

Allegion, the Allegion logo, Schlage and the Schlage logo are trademarks of Allegion plc. its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

## **About Allegion**

Allegion (NYSE: ALLE) is a global pioneer in seamless access, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion secures people and assets with a range of solutions for homes, businesses, schools and institutions. Allegion had \$2.7 billion in revenue in 2020, and its security products are sold around the world. For more, visit www.allegion.com



<sup>1</sup>SO glossy white style credentials are made from composite material, are printable, and can include a magnetic stripe as an option.

 $<sup>^2</sup>$  Add M1 to the model number for a magnetic stripe when ordering. Vertical slot punch not available on magnetic stripe cards.

<sup>&</sup>lt;sup>3</sup> Add SPV (vertical) or SPH (horizontal) your credential order for a slot punch. Vertical slot punch comes standard on all clamshell order. Vertical and horizontal slot punch are optional on ISO cards. Vertical slot punch not available on magnetic stripe cards.