

Multi-Technology Reader with Indala Support (SWH-4130)



Features That Make a Difference:

- Triple-receiver design allows simultaneous reading of HID® proximity cards, Indala® proximity cards, and contactless smart cards
- Reads more than 10 different types and formats of proximity cards and contactless smart cards, including most common Indala formats
- Download new functionality or enhancements for a future-proof solution
- Encryption and custom keys for secure transmission of data
- Mount on metal with optional isolation spacer
- Indoor/outdoor use
- Built-in tamper switch provides secure installation
- Plug-in screw terminals reduce installation time
- ISO compliant - 14443A, 14443B, 15693
- Lifetime warranty

Software House Multi-Technology Reader with Indala Support offers a unique, versatile single reader solution for reading both HID and Indala proximity cards simultaneously, while also reading multiple 13.56 MHz smart card technologies – including MIFARE® encrypted sectors – all with one reader. This powerful reader enables you to mix card populations of HID and Indala proximity cards without needing two separate readers, while also allowing a smooth, cost-effective transition to smart cards over time.

The reader continuously cycles between low and high frequency signals to read the presented card. Readers may be field-configured to enable or disable selected card formats and technologies.

The Multi-Technology Reader with Indala Support can be updated at any time with flash firmware. This saves significant time and money by allowing you to simply flash new card protocols or formats directly to the reader. The reader is configurable to read a specific encrypted MIFARE sector and block using standard or custom MIFARE read keys.

Important features such as a built-in tamper switch, two-piece connectors, and isolation spacers help reduce installation time. Coupled with robust environmental ratings and a lifetime warranty, the Software House Multi-Technology Reader with Indala Support is the clear choice for companies looking for a powerful, cost-effective way to use multiple card technologies.

Multi-Technology Reader with Indala Support

Physical

Dimensions (H x W x D) 111 x 84 x 28 mm
 (4.37 x 3.31 x 1.10 in)
 Form Factor Single-gang mounting
 Environmental (Interior/Exterior)-35° to 67°C (-31° to 151°F)
 0 to 100% relative humidity
 Index of Protection IP65
 Weight 0.34 Kg (12 oz.)
 Color Black
 Accessories Optional isolation spacer

Electrical

Power Requirements 9.6 to 16 VDC, 150mA maximum current
 Wiring Terminations Plug-in screw terminals

Wiring Details

Pin 1 External beeper control
 Pin 2 Ground
 Pin 3 Power (8 to 16VDC)
 Pin 4 D1 Wiegand
 Pin 5 D0 Wiegand
 Pin 6 Reserved for future use
 Pin 7 External green LED control
 Pin 8 External red LED control
 Pin 9 RS485/A – used for flash upgrade
 Pin 10 RS485/B – used for flash upgrade
 Pin 11 Tamper (normally closed)
 Pin 12 Tamper (normally closed)

Cable Recommendations 22 AWG [60 m (200 ft) max] or 18
 AWG [150 m (500 ft) max], stranded
 Operational

Read Range Up to 102 mm (4 in), depending on technology
 of card

Read Time Technology-dependent
 (typically < 300 msec)

Regulatory

FCC Part 15 Class C
 CE
 RoHS
 WEEE
 ISO 14443A, 14443B, 15693

Ordering Information

Model Numbers	Description
SWH-4130	Multi-Technology Reader with Indala Support, single-gang, black, ACC 37-bit format
SWH-4130-G	Multi-Technology Reader with Indala Support, single-gang, gray, ACC 37-bit format
SWH-4130-26B	Multi-Technology Reader with Indala Support, single-gang, black, 26-bit format
SWH-4130-G-26B	Multi-Technology Reader with Indala Support, single-gang, gray, 26-bit format
SWH-4130-37B	Multi-Technology Reader with Indala Support, single-gang, black, SWH 37-bit format
SWH-4130-G-37B	Multi-Technology Reader with Indala Support, single-gang, gray, SWH 37-bit format

Card Technology and Format Information

Card Technologies Supported

HID proximity
 Indala proximity
 MIFARE serial number
 DESFire® serial number
 ISO 14443A, 14443B, and 15693 serial number
 iCLASS® serial number
 MIFARE sector read

Communications

Wiegand data stream to controller
 Flashable via local RS-485

Proximity Configuration Using Program Card

Enable/disable specific proximity technology
 Indala formats supported:
 Wiegand 26-bit
 ACC 37-bit (default)
 SWH 37-bit
 (Note: only one Indala format is supported at any one time)

HID formats supported:

Wiegand 26-bit
 Corporate 1000 35-bit
 SWH 37-bit
 Pass-through HID formats

Smart Card Configuration Using Program Card

Pass-through output (128 bits, entire MIFARE block)
 Fixed length output (26-bit, 32-bit, 35-bit, 37-bit, 64-bit)
 MIFARE sector
 Select a sector (0-15); select a block (0-3)
 Customize encryption keys
 Specify data format (number of bits output)

Related Products



RM Readers



iSTAR Edge



iSTAR Pro

Approvals



www.swhouse.com

The trademarks, logos, and service marks displayed on this document are registered in the United States [or other countries]. Any misuse of the trademarks is strictly prohibited and Tyco International Ltd. will aggressively enforce its intellectual property rights to the fullest extent of the law, including pursuit of criminal prosecution wherever necessary. All trademarks not owned by Tyco International Ltd. are the property of their respective owners, and are used with permission or allowed under applicable laws.

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.
 © 2011 Tyco International Ltd. and its respective companies. All rights reserved. SH0152-DS-201108-R03-LT-EN