

SNCA-HRX550EXT

Outdoor dome camera housing



Applicable Camera Models;
- SNC-RX550P - SNC-RX530P - SNC-RX570P

Fixing Method;
- SNCA-WM20G (wall) - SNCA-CEILING (ceiling) -
SNCA-WM20FC (see note)

Rating;
- IP66

Operating Temperature;
- -29°C to +50°C - -44°C to +50°C with optional
heater/blower kit added (SNCA-HEATER)

Voltage;
- 24 volts AC

Optional accessories;
- SNCA-CLEAR/2 (included) - SNCA-TINTED/2 SNCA-
HEATER

Accessories

Mounting Hardware



SNCA-WM20FC

Wall mount for dome camera housings with fixed coupling attached



SNCA-CEILING

Mounting coupling for pendant applications



SNCA-WM20G

Wall mount for dome camera housings



SNCA-POLE30

Mounting pipe for pendant mount applications

Power supplies



SNCA-PS24-4

An indoor power supply with one 4 Amp 24V AC fused output.



SNCA-PS24-4E

An external power supply with one 4 Amp 24V AC fused output. Polycarbonate IP66 rated enclosure suitable for outdoor use.

Compatible Products

Pan Tilt Zoom

**SNC-RX530P**

Intelligent Network Camera with 216x zoom
- Black

**SNC-RX550P/WCE**

Intelligent Network Camera - White

**SNC-RX550P/BC**

Intelligent Network Camera with 312x zoom
- Black

**SNC-RX570P**

Intelligent Network Camera with DynaView
and 432x zoom- Black