



SNT-EX101

Single channel video surveillance encoder, utilising state of the art image transmission and enhancement technology

Video Surveillance Encoder

Designed for use in single channel applications the SNT-EX101 is a powerful, fully featured video encoder delivering a range of unique features. Converting traditional analogue video signals into digital video streams for transmission via IP-based networks, the SNT-EX series combines unrivalled network flexibility and enhanced imaging performance with advanced, intelligent video and audio analytics.

The SNT-EX series is the obvious choice when migrating from an existing analogue camera system to an IP based monitoring solution.

ONVIF (Open Network Video Interface Forum) compliance for easy interoperability with IP monitoring products from a variety of manufacturers.

1 Year PrimeSupport is included as standard within the EU, Norway and Switzerland. This gives users access to an expert helpdesk and, in the unlikely event of a failure, will arrange for an advance replacement unit to be delivered within a target time of one working day. An additional 2 years support is also available as an option.

Features

High resolution image quality in all conditions

Sony's unique XDNR (Excellent Dynamic Noise Reduction) and VE (Visibility Enhancer) and DSI (Dynamic Frame Integration) Technology come as standard features within the SNT-EX series of encoders. This unique image enhancing technology delivers superior noise free images in the most challenging conditions. By utilizing Sony's SNT-EX series with XDNR, VE and DFI technology, analogue cameras can now deliver superior imaging performance

Triple codec operation

The SNT-EX series supports three compression formats: JPEG, the best choice of high-quality still

images; MPEG-4, the format that provides clear moving images efficiently over limited-bandwidth networks; and H.264, the alternative for severely limited-bandwidth networks, providing twice the efficiency of MPEG-4. The camera can generate JPEG and MPEG-4 images simultaneously

Clear low-light images

XDNR (Excellent Dynamic Noise Reduction) technology virtually eliminates image blur in low-light conditions, enabling users to clearly capture images that have not been easy to portray in the past. It also overcomes the problems associated with many competitor camera models. What's more, when both XDNR and Visibility Enhancer are turned on, the cameras can achieve four times the sensitivity compared to when they are off. This technology is ideal for any outdoor surveillance monitoring, such as in a car park at night.

Improved performance in challenging lighting conditions

VE (Visibility Enhancer) technology improves performance in challenging lighting conditions, for example high-contrast environments, such as casinos and highways, that had previously been difficult to monitor. The Visibility Enhancer's advanced system suppresses extreme whites and boosts dark areas in a scene simultaneously and dynamically, to produce clearer images on the screen.

Improved performance from dynamic scenes

DFI (Dynamic Frame Integration) technology produces superior images from scenes containing both still and moving objects. DFI technology detects moving objects and reduces motion blur, simultaneously detecting stationary objects and reducing jagged edges. DFI delivers an optimized image with superior clarity and can be added to any analogue system by utilizing Sony's SNT-EX series.

Powerful Intelligent Video Analytics

Sony's SNT-EX Series encoder's include a complete IP surveillance solution based on its Distributed Enhanced Processing Architecture (DEPA™) platform. Intelligent video analytics automatically identify critical events for a high-level of security and to provide streamlined workflows. Unlike conventional monitoring solutions, the DEPA solution provides added intelligence to assist the surveillance operator in taking quick action. Users can precisely refine parameters for use in conjunction with the Intelligent Motion Detection and Intelligent Object Detection functions. By utilizing the SNT-EX series encoders, analogue cameras can now deliver the significant benefits offered by DEPA Advanced analytics

Tamper Alarm

When an attempt is made to tamper with the camera, such as spray-painting the lens, the SNT-EX Series detects this and triggers an alarm. This event can also be used to activate the camera relay, or even to start the Voice Alert function.

Advanced Audio Detection

Unlike conventional audio detection where an alarm is triggered based on a preset audio level, the SNT-EX Series triggers its alarms based on ambient sound conditions as the threshold. The camera stores and updates ambient audio levels and frequencies, and when the threshold level based on this data, is surpassed, an alarm is triggered.

Audio Message Alert

The encoder can store up to three pre-recorded audio alert messages which may be played via an active speaker upon manual or automatic initiation.

Versatile telemetry interface

The SNT-EX series offers support for control of 3rd party telemetry cameras. Maximum flexibility of control is offered via RS-422, RS-485 and Coaxitron interfaces.

Flexible streaming support

Video can be stored on optional USB memory media and then streamed using RTP/RTCP or RTSP protocols. This function is available with s/w version 1.1 or later.

Flexible recording and storage solutions

External storage is also possible using USB flash memory. Continuous, pre and post event video may stored in compressed format for later retrieval.

Support for IPv6

The SNT-EX Series supports Internet Protocol Version 6 (IPv6).

ONVIF Compliant

The ONVIF (Open Network Video Interface Forum) defines a common protocol for the exchange of information between network video devices including automatic device discovery, video streaming and intelligence metadata. Allows interoperability between network video devices. By utilizing Sony SNT-EX encoders, analogue systems can fully benefit from full ONVIF interoperability.

Benefits

The perfect analogue to digital migration solution from Sony

Sony's SNT-EX series encoders connect with existing analogue cameras to deliver flexible IP integration solutions. Crisp and clear CCTV images are available with Sony's advanced image processing technology. The SNT-EX101 offers enhanced levels of security even in the most challenging lighting conditions.

Highly flexible network capability

Enjoy exceptional operational flexibility using the ideal compression format for differing image and network types (JPEG for high quality still images; MPEG-4 and H.264 for clear, moving images over bandwidth-limited networks). Maximise network and storage resources by utilizing simultaneous dual-encoding of any two formats, from JPEG, MPEG-4 and H.264.

Optimum image quality when using traditional analogue cameras

By using Sony's SNT-EX range of encoders users can benefit from unrivalled image quality. State of the art image enhancing technology, that only Sony can offer, delivers clearer, brighter and higher quality images.

Simple to install, easy to maintain.

Compliance with ONVIF (Open Network Video Interface Forum) ensures interoperability and maximum flexibility between a wide range of manufacturers' network video products.

ONVIF compliance offers the optimum in system flexibility.

Compliance with ONVIF (Open Network Video Interface Forum) ensures interoperability and maximum flexibility between a wide range of manufacturers' network video products.

Technical Specifications**--Encoder Features--**

Visibility Enhancer	Yes
XDNR	Yes
Coaxitron control	Yes

--Interface--

Analog video input	x 1
Composite buffered through out	x 1
Ethernet	10BASE-T/100BASE-TX (RJ-45)
Serial Interface	RS-422/RS-485
USB Memory slots	x 1
Sensor input	x 2
Alarm output	x 2
Audio interface (IN/OUT)	IN x 1, OUT x 1
External microphone input	Mini-jack (Monaural), MIC IN/LINE IN: over 2.2kohm, 2.45VDC plug-in power
Audio line output	Mini-jack (Monaural), Max output level: 1.5Vp-p

--Image--

Codec image size (HxV)	D1 (NTSC: 720 x 480, PAL: 720 x 576), VGA (640 x 480), CIF (384 x 288), QVGA (320 x 240)
Video compression format	H.264, MPEG-4, JPEG
Maximum frame rate	H.264/MPEG-4/JPEG: 30fps (NTSC: 720 x 480, PAL: 720 x 576)

--Audio--

Audio compression	G.711/G.726
-------------------	-------------

--Scene analytics--

Intelligent motion detection	Yes (with built-in Post Filter)
Motion detection	No
Advanced audio detection	Yes

--Network--

Protocols	IPv4, IPv6, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, FTP (client/server), SMTP, DHCP, DNS, NTP, RTP/RTCP, RTSP, SNMP (MIB-2)
Number of clients	10
Authentication	IEEE802.1x
Number of IP address/Mac Address	x 1

--General--

Mass	Approx. 0.4 kg (14 oz)
Dimensions (W x H x D)	73 — 34 — 155 mm (2 7/8 — 1 3/8 — 6 1/8 inches)
Power requirements	AC24 V (In ±20%, Out)
Power consumption	9.6W max.
Operating temperature	0 to 50 °C
Storage temperature	-20 to 60 °C

--System Requirements--

Operating system	Microsoft Windows XP, Windows Vista
Processor	Intel Core2 Duo, 1.8GHz or higher

Memory	1GB or more
Web browser	Microsoft Internet Explorer Ver.6.0, Ver.7.0

--Supplied accessories--

Supplied accessories	CD-ROM (User's Guide and supplied programs) (1), Installation Manual (1), B&P Warranty Booklet (1), I/O port connector (1), 24 V AC connector (1), Attachment brackets (4), Attachment screws (8)
----------------------	---