## IP 2MP IP Vandal Resistant Corner Mount Color Camera with Advanced Analytics IP Encoder

# **O2607CM**

3.6mm lens with IP Encoder

## Features

- Supports up to Full HD 1080p @ 30fps
- Full HD resolution over coax
- Vandal resistant 90° corner mount camera
- Heavy duty housing is built to withstand blows from a 10 lb. sledgehammer
- 12VDC operation
- Additional analog output for 960H
- 5 year warranty

### **Camera Specifications**

Image Sensor	1/3" Progressive Scan CMOS, 2MP
Resolution	1920 x 1080
Effective Pixels	1984 (H) x 1105 (V)
Total Pixels	2000 (H) x 1121 (V)
Electronic Shutter	1/30 sec 1/30,000 sec.
Minimum Illumination	More than 50dB
S/N Ratio	Progressive
Video Output	1.0Vp-p / 75 ohms
Compression	H.265, H.264 (HP/MP/BP), MJPEG
Bitrate Control	VBR, CBR
Bitrate Range	64Kbps-8Mbps
Multiple Streaming	3 streams
Audio Compression	G.711A / G.711U
Power Supply	12VDC (power supply not included)
Housing	16 gauge steel
Dimensions	5.1" (W) x 3.3" (H)
Weight	1.5 lbs.
Communication	UTC

## Interfaces

Ethernet	10/100 Mbps
Power Input	DC jack
Power Output	12VDC Terminal block
Video Input	BNC
Audio Input	1CH 3.5mm
Audio Output	1CH 3.5mm
Storage	Micro SD slot, up to 256GB
Alarm	1 sensor input, 1 relay output (Terminal block)

## **Client Specifications**

Web Browser Support	Edge, Chrome, Firefox, Safari,
PC Application	SecureGuard <sup>®</sup> VMS/CMS, Speco Blue VMS
Mobile	Speco Blue App, SecureGuard <sup>®</sup> Mobile (iPhone® and Android™)



### **IP Encoder Operating & Unit Specifications**

Power	PoE, 12VDC (power supply not included)
Power Consumption	< 5.5W
Operating Temperature	-22°F - 140°F
Operating Humidity	10% - 95% relative humidity, Indoor-use only
Unit Dimensions	4.27" (W) x 3.45" (D) x 1.1" (H)
Unit Weight	9.5 oz
Certifications	FCC, RoHS

#### **Network Specifications**

Protocol	IPv4, IPv6, TCP, UDP, RTP, RTSP, HTTP, SMTP, FTP, DHCP
DDNS Support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/Mac address filtering, digest authentication
User Access	Max. 8 simultaneous users Actual number of users may vary depending on bandwidth

### **System Specifications**

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, object removal, abnormality, line crossing, intrusion, target counting, face detection, missing object detection, and heat map.
Alarm Triggers	Analytics
Alarm Events	FTP upload, email upload
Image Settings	Privacy mask, (8) region of interests, OSD



\*with compatible Speco recorder \*\*Products are in compliance with NDAA Section 889 Part B Guidelines



Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 12/4/23



