





# 2MP Intensifier IP® Discreet Ceiling Mounted Camera

## O2i562

3.6mm pinhole lens, white housing

### Features

- See color in low light without IR LEDs
- Supports up to 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- No problems caused by objects that reflect or absorb IR light sources
- With presets for different scenarios
- Attached cable (8 ft.) connects camera unit to main unit for flexible placement
- 2-way audio communication
- Sensor input and relay output
- Micro SD card slot (card not included)
- Conformant with ONVIF Profile S
- 5 year warranty\*



### Camera Specifications

Image Sensor	Progressive scan 1/2.8" CMOS, 2MP
Maximum Resolution	1920 x 1080
Minimum Illumination	F1.4, Color: 0.2 lux (Max Intensify)
White Balance	ATW/AWB
Compensation	WDR
Intensify	Selectable (max 8x) / Off
Electronic Shutter Speed	1/30 - 1/10000 sec
DNR	2D/3D

### Video Specifications

Main Resolution	1920x1080 / 1280x720 @ 30fps
Compression	H.264 (HP/MP/BP), MJPEG
Bitrate Control	VBR, CBR
Multiple Streaming	3 streams

### Audio Specifications

Mono Input/ Output	G.711
--------------------	-------

### External Terminal Specifications

Ethernet	10/100 Mbps
Alarm	1 sensor input, 1 relay output (terminal block)
Audio	1 mic in, 1 line out (terminal block)
Power	Terminal block

### Client Specifications

Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard® VMS
Mobile	SecureGuard® Mobile (iPhone® and Android™)

### Network Unit Specifications

Protocols	IPv4, TCP, UDP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, DNS
DDNS Support	Speco DDNS (free of charge)
Protocols	IPv4, TCP, UDP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, DNS
Security	User ID & Password protection, IP address filtering, digest authentication
User Access	Max. 8 simultaneous users Actual number of users may vary depending on bandwidth

### System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, tampering, sensor input
Alarm Triggers	Analytics
Alarm Events	FTP upload, email upload, micro SD card recording, relay output
Image Settings	Privacy mask

### Operating & Unit Specifications

Power Supply	PoE, 12VDC (power supply not included)
Power Consumption	4W
Operating Temperature	14° F - 122° F
Operating Humidity	0% - 90% RH
Main Unit Dimensions	2.59" (W) x 1.24" (H) x 4.21" (D)
Main Unit Weight	5 oz.
Camera Unit Dimensions	3.4" (Dia) x 1.6" (H)
Camera Unit Weight	5 oz.
Certifications	FCC, RoHS

### Optional Accessories



POEINJ  
25.5W  
PoE Injector



PSW5  
12VDC  
Power Supply



\*Products are in compliance with NDA Section 889 Part B Guidelines

