

4MP Flexible Intensifier® IP Dome Camera with Advanced Analytics, NDAA

04FD2

2.8mm fixed lens, dark gray housing

















Features

- Flexible Intensifier® Technology to fit any lighting application
- Captures up to 4MP @ 30fps real time
- Captures color in extreme low light conditions and monochrome in absolute darkness.
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Micro SD card slot (card not included)

- Conformant with ONVIF Profile G/S/T
- IP67 Weather Resistance
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection*
- Face/Person/Vehicle detection*
- Junction box included
- 5 year warranty





Camera Specifications		
Image Sensor	Progressive scan 1/1.8"CMOS	
Maximum Resolution	2560 × 1440	
Field of View	Horizontal: 111.3°; Vertical: 78.9°; Diagonal: 118.4°	
Minimum Illumination	0.0016 lux@F1.6, AGC ON; 0 lux with IR	
White Balance	Auto, Indoor, Outdoor, Manual	
Compensation	True WDR (120dB), BLC, HLC	
Day/Night	Smart IR	
Electronic Shutter Speed	1s~1/100000s	
DNR	3D DNR	
Angle Adjustment	Pan 0° ~ 355°, Tilt 0° ~ 67°, Rotation 0° ~ 180°	

Video Specifications		
Main Resolution	2560×1440, 2304×1296, 1920×1080, 1280×720, D1, CIF, 480×240 @30fps	
Substream	1280x720, D1, CIF, 480×240 @30fps	
Third Stream	D1, CIF, 480×240 @30fps	
Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG	
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)	
Multiple Streaming	3 streams	
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Exposure, Gain, Corridor Pattern, Image flip/mirror	

Aud	lio	Sn	eci	fica	tions	
AUU	110	JΡ	CCI	IICU	110113	•

Audio Compression	G.711A / G.711U	
Audio input	Built-in mic and 3.5mm input	
Audio output	No	
Client Specifications		
Web Browser Support	Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari	
PC Application	SecureGuard® VMS and SecureGuard CMS	
Mobile	SecureGuard® App, Speco Blue	

Interfaces

Ethernet	RJ45 Jack, 10/100 Mbps, PoE
Power	12VDC input jack
Audio	Buit-in mic and 3.5mm input
Card slot	MicroSD, up to 256GB (not included)
Alarm	1ch input/ 1ch output
Reset	Yes

Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication, Watermark, and illegal login lock
User Access	Max. 10 simultaneous users Actual number of users may vary depending on bandwidth

System Specifications

7		
PoE	Standard (IEEE 802.3af)	
Analytics	Motion detection, Object abandoned/missing detection, region entrance/exiting/intrusion detection (people/vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection, face detection, face capture.	
Alarm Triggers	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection	
Alarm Events	FTP upload, email upload	

Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	5.5W (max)
Operating Temperature	-40°F - 140°F
Operating Humidity	less than 95% (non-condensing)
Unit dimensions	4.68" (φ) x 3.5" (H)
Unit Weight	1.43 lbs
Certifications	FCC

^{*}with compatible Speco Blue recorder



Optional Accessories







Pole Mount



FMT1

Flush Mount



25.5W

PoE Injector





Cameras Interfaces





















ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Spec Rev. 7/20/23

Wall Mount Corner Mount













^{**} Compliant with NDAA Section 889 Part B Guidelines