

slimline magnets



A range of magnets that provides a wide number of options

TDSi offers a comprehensive range of high quality electromagnetic door locking products that are suitable for a multitude of applications.

Featuring a 600 lb holding force, these locks provide you with a cost effective, high security locking solution for your access control systems.

The slimline range is available in both single and double formats, with or without lock monitoring, and is backed by a full range of complementary brackets, including attractive architectural options.

All products are supplied in an attractive finish and are fast and easy to install.

slimline magnets

DS0037_Issue 3

SPECIFICATIONS

TDSi Part No.	2921-0200	2921-0201	2921-0204	2921-0205
Format	Single		Double	
Monitored	No	Yes	No	Yes (single)
Holding Force	600 lb		2 x 600 lb	
Supply Voltage	12 V DC or 24 V DC (selectable)			
Nominal Current	500 mA (12 V DC) or 250 mA (24 V DC)		1000 mA (12 VDC) or 500 mA (24 V DC)	
Connection	Fixed rising clamp type			
Lock Dimensions	26 x 350 x 48 mm		26 x 700 x 48 mm	
Armature Dimensions	12 x 185 x 38 mm			
Weight	2 kg		4.2 kg	

FEATURES & BENEFITS

Suitable for use in a wide-range of applications

This range of products offers you full flexibility in terms of both aesthetic and installation options through a comprehensive selection of locks and brackets.

Range of input voltages

These locks can be connected to either 12 V DC or 24 V DC power supplies allowing them to be used in all door locking applications.

No residual magnetism

Prevents the door from sticking shut when the lock is released.

Can be fitted to a variety of door thicknesses

The locks can be fitted to doors between 35 and 53mm thick.

Full range of mounting brackets available

Choose from a full range of brackets to suit your particular requirements including architectural options.

Anodised aluminium housing

Provides an attractive and corrosion-resistant finish.


Armature kick-off button

Ensures that the armature plate dis-engages from the magnet immediately when the lock is released.


Safety bolt feature

Prevents the magnet from becoming detached from the top plate, eliminating the risk of personal injury from a falling magnet.

BRACKET OPTIONS



L Bracket for outward opening doors



Z&L Bracket for inward opening doors

ORDERING INFORMATION

- 1 **Part Number: 2921-0200**
Description: Slimline single door magnet
- 2 **Part Number: 2921-0201**
Description: Slimline single door magnet with lock monitoring
- 3 **Part Number: 2921-0204**
Description: Slimline double door magnet

Part Number: 2921-0205
Description: Slimline double door magnet with lock monitoring feature
- 4 **Part Number: 2921-0220**
Description: L&Z bracket for slimline door magnets for inward opening doors
- 5 **Part Number: 2921-0221**
Description: L bracket for slimline door magnets for outward opening doors

Part Number: 2921-0226
Description: Architectural L&Z bracket for slimline door magnets for inward opening doors

Part Number: 2921-0227
Description: Architectural L bracket for slimline door magnets for outward opening doors
- 6 **Part Number: 2921-0224**
Description: Surface mounted armature housing for slimline door magnets
- 7 **Part Number: 2921-0228**
Description: Flush mounted armature housing for slimline door magnets



TDSi UK
Unit 10 Concept Park,
Innovation Close,
Poole,
Dorset BH12 4QT
United Kingdom
t: +44 (0)1202 723535
f: +44 (0)1202 724975
e: sales@tdsi.co.uk

TDSi France
Immeuble ATRIA,
2 rue du Centre,
93160 NOISY LE GRAND,
France
t: +33 (0)1 58 84 20 90
f: +33 (0)1 58 84 20 91
e: infos@tdsi-france.com

TDSi China
Rm 103, 1 Bld,
Shangsha Innovation Science
& Technology Park,
9283 Binhai Road,
Futian District,
Shenzhen 518048,
P.R.China
t: 86-755-82535725,
82535720
f: 86-755-82535770
e: tdsiinfo@microgarde.com.cn