



# MIFARE® Readers

**exsmart<sup>2</sup>** is a range of **high-performance** contactless MIFARE® smart card readers from TDSi. Available with or without a backlit tactile keypad, **exsmart<sup>2</sup>** is designed to be mounted in a standard electrical back-box making for a **neat** and **simple** installation. All products are supplied with a choice of covers allowing the look of the reader to be changed to suit its surroundings.



## Overview of the **exsmart<sup>2</sup>** reader

### Features

- Mounting into a standard electrical back-box
- Tough plastic clip-on covers in both graphite and light grey
- Supports the 2 Reader Mode of **microgarde** access control units
- Available with a blue backlit keypad
- Pluggable terminal block cable termination
- Fully encapsulated design
- Integral LEDs and sounder
- Industry standard outputs
- Read range of 50 mm (nominal)

### Benefits

- Neat installation into a standard fitting
- Adapt the look of the reader to suit the surroundings
- Use **microgarde** to control 2 doors both with read-in/read-out. Saves on hardware, installation time and cost.
- Increase security by adding a PIN to your card-based access control
- Allows the cable to be pre-wired prior to installation of the reader for convenience
- Provides maximum protection against water ingress making it suitable for mounting both indoor and out
- Gives the user unambiguous audible and visual indication of card reads and access status. Maximises user confidence
- Allows connection to all standard access control panels
- Easy to use



**exsmart<sup>2</sup>** K MIFARE® reader with keypad


**exsmart<sup>2</sup>**

**TDSi**  
ACCESS EVERYWHERE

w: [www.tdsi.co.uk](http://www.tdsi.co.uk)  
e: [sales@tdsi.co.uk](mailto:sales@tdsi.co.uk)  
t: +44 (0)1202 723535



# MIFARE® Readers



## Technical Data

<b>Dimensions</b>	102 x 102 x 20 mm. Connector including terminal block protrudes by 11 mm from rear face.
<b>Weight</b>	270 g
<b>Operating environment</b>	-20°C to +55°C, 0 to 95 %RH (non-condensing)
<b>Power supply</b>	9 to 16 VDC, 100 mA max
<b>Operating frequency</b>	13.56 MHz (nominal)
<b>Card technology</b>	ISO14443-A: MIFARE Standard (1k) MF1 ICS50, MIFARE (4k) MF1 ICS70
<b>Sounder</b>	Integral with external control
<b>LEDs</b>	2 -red and green both with independent external control. Bi-colour input capability for connection to TDSi access control units.
<b>Read range</b>	50 mm (nominal) with ISO card
<b>Output formats</b>	Mag stripe, 26-bit Wiegand

## Ordering Information

### Part Number: Product Description:

5002-0435	exsmart <sup>2</sup> MIFARE® CSN reader
5002-0436	exsmart <sup>2</sup> MIFARE® CSN reader with keypad
2920-3000	Compatible ISO 1K MIFARE® card—plain white
2920-3001	Compatible ISO 4K MIFARE® card—plain white
2920-3002	Compatible ISO 1K MIFARE® card—white with serial number printed
2920-3003	Compatible ISO 4K MIFARE® card—white with serial number printed

# exsmart<sup>2</sup>



w: [www.tdsi.co.uk](http://www.tdsi.co.uk)  
 e: [sales@tdsi.co.uk](mailto:sales@tdsi.co.uk)  
 t: +44 (0)1202 723535

Time and Data Systems International limited  
 Registered office: 99 Holdenhurst Road, Bournemouth  
 BH8 8DY  
 Registered in England: 1585167

