


Benefits

- Flexible configuration
- Hot stand-by disks
- RAID support
- Multiple arrays configurable with dedicated or global hot spares
- RAID levels supported: 0, 1, 5 and 6
- Easy expansion by: Adding new drives or replacing drives with drives of larger capacity



The System Storage is delivered in dense 12 drive 2U enclosure.

S-VMX System Storage is an external storage component of Teleste video system. The unit is directly attached storage (DAS) matrix featuring high capacity SAS host interfaces and performance optimised NearLine SAS disk drives.

S-VMX System Storage unit can be attached to any VMX system component


with storage capabilities and support for a SAS Host Controller.

S-VMX System Storage component is scalable to different storage capacities and RAID levels. It can be equipped with 1TB, 2TB or 3TB hard drives to match the specific storage needs.

On system level there is support for different architectures to either to maximise the storage capacity or the redundancy of the system.

The unit is equipped with redundant fans and power supply. Support for redundant connectivity or sharing between two NVRs can be obtained with the optional second management module.

S-VMX System



Technical specifications (Typical values unless otherwise stated)

Hardware			Relative humidity		Non-condensing	
Interfaces	1 x SAS 2.0, 6Gbps 1 x SAS 2.0, 6Gbps	Input Output	8...80%	28.39kg (62.6lbs) 8.84kg (19.5lbs)	Max. Empty	
Power supply	2 x 600W	Redundant, hot-swap	Dimensions: 640.0 mm (25.20") 602.0 mm (23.70") 19" 2U Top view VHD100 series Side view			
Bays	12					
HDD	1TB, 2TB, 3TB	NearLine SAS, SAS				
RAID levels	0, 1, 5, 6					
System						
Host connectivity	up to 8 units up to 4 units 1 unit	Non-redundant mode Redundant mode Split mode				
General (*10% of annual operating hours, ** 1% of annual operating hours)						
Supply voltage	100...240VAC	Auto-sensing				
Power consumption	300W	Max.				
Heat dissipation	2313 BTU/hr	Based on PSU max wattage				
Operating temperature	+10...+35°C (50...95°F) +5...+40°C (41...104°F)* -5...+45°C (23...113°F)**					
Storage temperature	-40...+65°C (-40...149°F)					

Ordering codes (Suite 2.2)

SES121 - 16	S-VMX System Storage	16TB
SES121 - 20	S-VMX System Storage	20TB
SES121 - 24	S-VMX System Storage	24TB
SES131 - 24	S-VMX System Storage	24TB
SES131 - 30	S-VMX System Storage	30TB
SES131 - 36	S-VMX System Storage	36TB

Option:
VHD090 Redundant EMM Kit for VHD100 Series

Hardware services ordering codes

VSD131	VHD100 series HW, on-site diagnosis service for 3 years
VSD141	VHD100 series HW, on-site diagnosis service for 4 years
VSD151	VHD100 series HW, on-site diagnosis service for 5 years
VSD132	VHD100 series HW, data protection service for 3 years
VSD142	VHD100 series HW, data protection service for 4 years
VSD152	VHD100 series HW, data protection service for 5 years
VSD140	VHD100 series HW warranty extension from 3 years to 4 years
VSD150	VHD100 series HW warranty extension from 3 years to 5 years