

Intrusion Detectors  
 External Motion Detectors  
 PIR External Motion Detectors



Type

Order No.

IS405H

**External PIR detector long range curtain, 150 x 3.3 m, 3 zones high performance**

S54533-F107-A100



The IS405H is suitable for outdoor environment. Switches enable easy and quick set-up. Ideal for activating a combined video surveillance system for curtain detection. ISMD42 is used for mounting. Separate transistor output per detection zone.

Supply	10.5 ~ 30 VDC / 24 VAC (+/-15%)
Current consumption	Typ. 18 mA @ 12 VDC / 10 mA @ 24 VDC
Alarm relay output (NO/NC)	30 VDC, max. 250 mA NC
Open collector output	Open collector NPN, 30 VDC, max. 50 mA
Sensitivity adjustment	DIP switches and RS485
Tamper switch	30 VDC, 100 mA
Communication	Bi-directional RS 485 @ 9,600 baud
Optical system	Precision glass mirror
Walking speed	0.20 to 5.00 m/s
Front window	Silicon, IR transmissive
Installation height	2.50 to 4.00 m
Operating temperature	-40 ~ +60 °C
Heated mirror optics	Yes
Dimensions	Ca. 100 x 128 x 272 mm
Weight	Ca. 0.900 kg

3