



M43

Access Control

SiPass Entro PIN reader

- Group code level
- PIN code function
- Sturdy construction for outdoor and indoor use

In an Entro system, the M43 is used primarily in two situations: when you only require the group code level in the system, or when you want to add a PIN code function to an existing hands-free reader like HF500-Cotag.

Technical data

M43	
Interface to controller	BC-Link
Operating voltage	12 to 24 VDC, powered from controller
Current consumption	50 mA
Indicators	3 x LED (red/yellow/green) 1 x Buzzer
Environment	Indoor or outdoor use (IP54design). In very exposed locations, use SH2 or SH1 rain cover
Operating temperature	-35 to +50 °C
IP rating	IP54
Housing	Cast metal with stainless steel keys and security lock.
Colour	Grey
Dimensions (WxHxD)	80 x 140 x 40 mm
Keypad	Stainless steel keys 0-9, A, B
Approval	CE
Inputs	Tamper switch for internal alarm

Details for ordering

Type	Part no	Designation	Weight
M43	S24246-F8400-A1	M43 PIN reader	0.75 kg

Issued by
Bewator AB
SE-171 24 Solna
Sweden

www.buildingtechnologies.siemens.com

© 2008 Copyright by
Bewator AB, a Siemens company
Data and design subject to change without notice.
Supply subject to availability.

Document no. **A6V10081483**
Edition 04.2008