

# Nextiva

## S5120 Day/Night IP Dome Cameras with H.264 and Auto-Focus Technology



### At A Glance:

- Feature-rich 1080p H.264 IP dome camera with 3x remote zoom for indoor video surveillance
- Superior day/night functionality via automatic, removable IR-cut filter
- Advanced auto-focus technology provides crisp detail in any video application
- Multi-stream H.264 video compression for optimal use of bandwidth and storage
- Compatible with Nextiva Video Management software and the Nextiva EdgeVR network video recorder

Nextiva® S5120 day/night IP cameras incorporate advanced H.264 compression and 1080p high-definition resolution to deliver crystal clear images, ultra-efficient bandwidth management and excellent performance in a variety of discreet video surveillance applications.

### Optimum Performance in Day/Night Applications

These professional IP dome cameras feature high-definition 1080p 2.0 megapixel resolution streamed at 30fps and are designed to accommodate a wide range of discreet video surveillance requirements. They provide excellent video quality in both day and night conditions, with an IR cut filter that is automatically removed for optimum image clarity in low-light environments or where secondary infrared illumination is used. The Nextiva S5120 combines cutting-edge imaging capabilities with advanced auto-focus lens technology and up to 3x remote zoom. Dual streaming and advanced H.264 compression help optimize use of valuable bandwidth and storage. Additionally, settings such as compression and frame rate can be defined to change automatically based on alarms, motion, time of day, or other events, for greater situational awareness and more effective video surveillance.

### Easy Implementation for Indoor Surveillance Applications

Nextiva S5120 day/night IP cameras are designed for easy, secure, and cost-effective installation. Full 802.3af Power-over-Ethernet reduces wiring and installation costs, and support for 12V DC or 24V AC enables these cameras to be readily retrofitted into existing systems to facilitate migration to IP. S5120 day/night cameras also feature on-board camera storage and bi-directional audio support for more effective video operations. These cameras can be configured using an on-board Web browser interface, Nextiva EdgeVR® or Nextiva Control Center.

### Powered by Nextiva

Nextiva S5120 IP cameras are fully integrated with Nextiva video management software — centralized device management, automated health monitoring, remote video viewing, and more — and with other Nextiva solutions, including the Nextiva EdgeVR IP-based network video recorder.

Nextiva is the industry's broadest IP video portfolio, a single source for virtually every facet of your video operations — from cameras, encoders, and network video recorders to video viewing management, physical security information management and analytics software. Designed to enhance any video network, Nextiva streamlines management of large, geographically dispersed video operations and helps organizations realize the benefits of IP video using their legacy video investments.

# TECHNICAL SPECIFICATIONS

## S5120FD-DN — Day/Night IP Dome Cameras

VIDEO	
• Imaging	1/2.7" CMOS
• Effective Pixels (HxV)	1920(w) x 1080(h)
• Day/Night Support	Automatic removable IR cut filter
• Analog Out	Full-time 1/8" (3.5mm) jack. BNC adapter supplied, configurable to NTSC or PAL
• Minimum Illumination	0.1 Lux Day Mode, 0.06 Lux Night Mode (w/ IR cut filter removed), 0.00 Lux Night Mode (with external IR illumination and IR Cut filter removed)
• Analog Video Output	Full-time with supplied BNC adapter
• Dynamic Range	69dB
• Compression	H.264, MPEG-4, MJPEG
• Resolution	Scalable from 320x240 to 1920x1080
• Frame Rate	1-30fps
• Bandwidth	Configurable 40Kbps to 8Mbps
• Max Streams	2 with each stream configurable for resolution, fps and compression type
• Tuning	Configurable max exposure time, compression level, brightness, contrast, sharpness, saturation and exposure bias
• Gain Control	AGC
• White Balance	Automatic, Locked
• Backlight Compensation	Automatic BLC
LENS	
• Type	3X with auto-focus and remote zoom
• Optical Zoom	3X
• F-Stop Range	F1.2 ~ F2.1
• Focal Length	3-9mm
• View Angle	31.7° ~ 93.0° (horizontal)
• Minimum Working Distance	10cm
NETWORK	
• Interface	Ethernet 10/100 Base-T
• Connector	RJ-45 Jack
• Protocols	IPv4, IPv6, TCP/IP, HTTP, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, CoS, QoS, SNMP and 802.1X
• Security	SSL-based authentication
PORTS	
• Power Input	12V DC (2-pin terminal), 24V AC (2-pin terminal), IEEE 802.3af PoE (RJ-45)
• Audio	3.5mm (1/8")
• Storage	Micro SD/SDHC card slot - up to 32GB
• Serial	N/A
• Alarm Input / Output	Digital in/out (4-pin terminal)
• Power Consumption	5.8W
PHYSICAL	
• Dimensions	Ø6.3 x 4.3H in (Ø159.3 x 109H mm)
• Weight	1.8 lbs (828g)
• Operating Temperature	32° - 122° F (0° to 50° C)
• Humidity	0% to 90% relative, non-condensing
• Camera Mount	Surface mount (pendant, recess and wall mount options)
• Enclosure	Surface mount indoor dome
MANAGEMENT	
• Configuration	Nextiva, Sconfigurator, or Internet Explorer 9.0
• Multi-Language Support	English, Spanish, French, German, Chinese
• Firmware Upgrade	Flash memory for upgrade of application firmware over the network. Mass update supported by Nextiva and EdgeVR.
CERTIFICATION & REGULATION	
• USA	FCC Part 15 (Subpart B, Class A)
• Canada	ICES-003/NMB-003 Class A
• Europe	CE Marking (EN55022, EN55024), GOST
• China	CCC

### About Verint Video Intelligence Solutions

Verint® Video Intelligence Solutions™ is the leading global provider of networked video solutions designed to enhance the security of people, property and assets. Its award-winning Nextiva® portfolio features IP video and physical security information management software, integrated analytics, encoders, cameras, wireless devices and intelligent NVRs for use across a variety of vertical market environments. Open, standards-based and IT friendly, Verint solutions help organizations realize the benefits of IP video leveraging their legacy video investments.

### Verint. Powering Actionable Intelligence.®

Verint® Systems Inc. (NASDAQ: VRNT) is a global leader in Actionable Intelligence® solutions and value-added services. More than 10,000 organizations in over 150 countries use our workforce optimization and security intelligence solutions to improve enterprise performance and make the world a safer place. Verint is a member of the US broad-market Russell 3000 Index. For more information about Verint, visit [www.verint.com](http://www.verint.com).



[videoinfo@verint.com](mailto:videoinfo@verint.com)  
1-866-NEXTIVA

330 South Service Road  
Melville, NY 11747 USA

[www.verint.com/videosolutions](http://www.verint.com/videosolutions)

Unauthorized use, duplication, or modification of this document in whole or in part without the written consent of Verint Systems Inc. is strictly prohibited.

By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

Features listed in this document are subject to change. Please contact Verint for current product features and specifications. All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners.

© 2012 Verint Systems Inc.  
All Rights Reserved Worldwide.

February 2012