Nextiva
IP Cameras

Which Nextiva IP Camera is Right for You?

CAMERA	V3320 Economic Box	V3320 Economic Mini Dome	V3320 Economic Vandal Dome	V3320 Economic Recess Dome	V4320 WDR Box	V4320 WDR Indoor Mini Dome	V4320 WDR Vandal Dome	V5620PTZ 18X HD PTZ
DESCRIPTION	1080p box camera with high-definition resolution	1080p indoor dome camera with IR illuminator	1080p outdoor weather/vandal dome camera with IR Illuminator	Small in size and price, but heavy on performance 1080p recess mount mini-dome	1080p 96+ dB Wide-Dynamic Range box camera	1080p 96+ dB Wide-Dynamic Range indoor dome with auto focus and IR Illuminator	1080p 96+ dB Wide-Dynamic Range IP66 Vandal dome with auto-focus and IR illuminator	High-definition 1080p pan-tilt-zoom IP camera with 18X zoom
ENCLOSURE TYPE	Fixed "box" camera	Fixed surface mount mini dome	IP66 Vandal Dome	Fixed recess mini dome	Fixed "box" camera	Fixed surface mount mini dome	IP66 Vandal Dome	PTZ (indoor & outdoor versions)
SENSOR	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.7" CMOS
RESOLUTION	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel
LENS	C/CS Mount compatible (lens not included)	3-9mm Varifocal	3-9mm Varifocal	2.5mm (-L2) 3.4mm (-L3) 6.0mm (-L6)	C/CS Mount compatible (lens not included)	3-9mm Motorized	3-9mm Motorized	4.7-84.6mm (18X)
MAXIMUM PERFORMANCE	1080p @ 30 FPS	1080p @ 30 FPS	1080p @ 30 FPS	1080p @ 30 FPS	1080p @ 60fps	1080p @ 60fps	1080p @ 60fps	1080p @ 30 FPS
STREAMING	Triple	Triple	Triple	Dual	Triple	Triple	Triple	Triple
AUDIO	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)	In/Out uLAW (G.711)	in/out uLAW (G.711)	in/out uLAW (G.711)	in/out uLAW (G.711)	In/Out uLAW (G.711)
VANDAL/ WEATHER RESISTANT	No	No	Yes, IP66	No	No	No	Yes, IP66	Yes, IP66
POWER OVER ETHERNET SUPPORT	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE	802.3at, Class IV PoE
3-AXIS LENS ROTATION	No	Yes	Yes	No	No	Yes	Yes	N/A
MOUNT TYPE	1/4" x 20 top and bottom Mounts	Surface, Recess, Pendant, Wall	Surface, Recess, Pendant, Wall, Pole	Indoor Recess	1/4" x 20 Top/Bottom	Surface, Recess, Pendant, Wall	Surface, Recess, Pendant, Wall, Pole	Surface, Pendant, Wall, Pole, Recess
ALARM I/Os	Yes 2/2	Yes 2/2	Yes 2/2	No	Yes 2/2	Yes 2/2	Yes 2/2	Yes 2/2

CAMERA	S5120 Box	S5120 Indoor Dome	S5120 Vandal Dome	S5250 Box	S5250 Indoor Dome	S5250 Vandal Dome	S5503PTZ Standard Definition PTZ
DESCRIPTION	1080p H.264 box camera supporting C/CS mount lenses and Agent VI analytics capability	1080p H.264 indoor dome with auto-focus, 3X remote zoom and Agent VI analytics capability	1080p H.264 IP66 vandal dome with auto-focus, 3X remote zoom and Agent VI analytics capability	Ultra-high 5 megapixel H.264 box camera with multi-megapixel rated C/CS mount lens	Ultra-high 5 megapixel H.264 indoor dome with auto-focus and 3X remote zoom	Ultra-high 5 megapixel H.264 IP66 vandal dome with auto-focus an 3X remote zoom	VGA IP PTZ with H.264 compression that functions both IP and analog environments
ENCLOSURE TYPE	Fixed "box" camera	Fixed surface mount mini dome	Fixed surface mount vandal/weather mini dome	Fixed "box" camera	Fixed surface mount mini dome	Fixed surface mount vandal/weather mini dome	PTZ (recess, indoor pendant and outdoor pendant versions)
SENSOR	1/2.7" CMOS	1/2.7" CMOS	1/2.7" CMOS	1/2.5" CMOS	1/2.5" CMOS	1/2.5" CMOS	1/3" CMOS
RESOLUTION	1080p 2 Megapixel	1080p 2 Megapixel	1080p 2 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	VGA
LENS	C/CS Mount compatible	3-9mm Auto-focus 3X Remote Zoom	3-9mm Auto-focus 3X Remote Zoom	2.8-12mm C/CS Mount Auto-Iris	3-9mm Auto-focus 3X Remote Zoom	3-9mm Auto-focus 3X Remote Zoom	4.1 - 73.8mm (18ID) 3.5-98mm (28DW) 3.4 - 122.4mm (36DW)
MAXIMUM PERFORMANCE	1080p @ 30 FPS	1080p @ 30 FPS	1080p @ 30 FPS	5 MP @ 7 FPS	5 MP @ 7 FPS	5 MP @ 7 FPS	VGA @ 30 FPS
STREAMING	Triple	Triple	Triple	Triple	Triple	Triple	Dual
AUDIO	Yes	Yes	Yes	Yes	Yes	Yes	Yes
VANDAL/WEATHER RESISTANT	No	No	Yes	No	No	Yes	Yes
POWER OVER ETHERNET SUPPORT	Yes	Yes	Yes	Yes	Yes	Yes	24V AC Only
3-AXIS LENS ROTATION	N/A	Yes	Yes	N/A	Yes	Yes	N/A
MOUNT TYPE	1/4" x 20 top and bottom mounts	Surface, Pendant, Wall, Recess	Surface, Pendant, Wall, Pole, Recess	1/4" x 20 top and bottom mounts	Surface, Pendant, Wall, Recess	Surface, Pendant, Wall, Pole, Recess	Surface, Pendant, Wall, Pole, Recess, Parapet
ALARM I/Os	Yes	Yes	Yes	Yes	Yes	Yes	Yes

About Verint Systems Inc.

Verint® (NASDAQ: VRNT) is a global leader in Actionable Intelligence® solutions. Actionable Intelligence is a necessity in a dynamic world of massive information growth because it empowers organizations with crucial insights and enables decision makers to anticipate, respond and take action. Verint Actionable Intelligence solutions help organizations address three important challenges: customer engagement optimization; security intelligence; and fraud, risk, and compliance. Today, more than 10,000 organizations in over 180 countries, including over 80 percent of the Fortune 100, use Verint solutions to improve enterprise performance and make the world a safer place. Learn more at www.verint.com.

VERINT®

info@verint.com
1-800-4VERINT

330 South Service Road
Melville, NY 11747 USA

www.verint.com/videosolutions