



## CD41 Indoor Dome Tech Specs

<b>Sensor Resolution</b>	5MP (2688 x 1944)	<b>Focal Length</b>	f=2.8mm
<b>Lens Type</b>	Fixed	<b>Iris</b>	Fixed
<b>Image Sensor</b>	1/2.8" Progressive CMOS	<b>Aperture</b>	F1.6
<b>IR Range</b>	15m / 50ft in low light	<b>Resistance Rating</b>	Rating IK08, FCC, IEC60950-1
<b>Field of View</b>	Horizontal: 97° Vertical: 71° Diagonal: 128°	<b>Operating Specs</b>	Power: 11W (IEEE 802.3af PoE) Temperature: -10°C-50°C (14°F-122°F) Humidity: 90%
<b>Dimensions</b>	With mount plate: Ø: 146mm / 5.75in, H: 104.3mm / 4.11in ; 736g / 25.96oz Without mount plate: Ø: 146mm / 5.75in, H: 99.8mm / 3.93in ; 593g / 20.92oz	<b>Connectivity</b>	Ethernet: 10/100Mbps RJ-45 cable connector for Network/PoE connection

SKU	Max Days of Retention	Onboard Storage
CD41-30-HW	30	128GB
CD41-30E-HW	30	128GB
CD41-60-HW	60	256GB
CD41-60E-HW	60	256GB
CD41-90-HW	90	384GB
CD41-90E-HW	90	384GB
CD41-120-HW	120	512GB
CD41-120E-HW	120	512GB
CD41-365-HW	365	2TB
CD41-365E-HW	365	2TB