VICON HPOE-100 CAMERA HOUSING ACCESSORY

UPoE Midspan Injector






The HPOE-70W-INJ is a UPOE injector that uses the same cabling standard as PoE. Instead of delivering power over two twisted pairs, it provides the capability to source up to 60W of power by using all the four pairs of standard Ethernet cabling (Cat5e or better).

The architecture for a 4-pair system is an extension of the 2-pair design.





System Features

Gigabit Ethernet 1 RJ45 Port


Standards IEEE 802.3/802.3u/802.3ab

Power Input 100-240 VAC
POE Power Output 60W (1 Port)
802.3at Standard Compatible
802.3af Standard Compatible


Power Pin Assignment 1/2 (-) 3/6 (+) 7/8 (-) Operating Temperature $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ ($32^{\circ}\text{F} \sim 122^{\circ}\text{F}$) External Dimensions 153 (L) \times 84 (W) \times 44 (H) mm

Weight 0.4 Kg

Dimensional Drawings



Connection to HPOE-100 Housing



Ordering Information

Description Model Number

Midspan Gigabit POE Injector for HPOE-100. UPOE Output: 60W. Input 100-240 VAC,

Data Sheet Number: V278-00 Dated: 06/2016

Vicon Data Sheet Part Number: V278-00/8009-7278-00-00 Specifications subject to change without notice.

Vicon and their logos are registered trademarks of Vicon Industries Inc. Copyright © 2015 Vicon Industries Inc. All rights reserved.

