

DSMH26LED-WGF

26" Active Matrix Metal Cased Glass Fronted TFT LED High Resolution

DSMH26LED-WGF

Panel Type	26" Active Matrix Glass Fronted TFT LED High Resolution
Case Type	Metal
Maximum Resolution	1920(H) x 1080(V)
Active Display Area	576 (H) X 324 (W) mm
Pixel Pitch	0.1 (H) x 0.3 (V) mm
Bezel Thickness	Sides: 22.3mm Top: 22.3mm Bottom: 34.4mm
Contrast Ratio	800 : 1 Ratio
Brightness	400 cd/m ²
Response Time	1.5 - 3.5ms
Viewing Angle	U/D: 75° / 75°, L/R: 80° / 80°
Display Colours	16.7 M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9 With 4:3 Function
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1 Left x 1, 5W
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Yes

IN/OUT INTERFACE

Video Interface	HDMI x1 VGA x 1 BNC x 2 In / BNC x2 Out, S-Video
Audio Interface	Audio in x 1, Audio L x 1, Audio R x 1
Power Interface	AC 100 -240v In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS / WEEE
Vesa Standard Mount	200 x 200mm
Stand Type	Desktop
Colour	Black
Button Position	Front, Right
Packing Dimension	770 (W) x 600 (H) x 360 (D) mm
NET Weight	10.8 Kg
GROSS Weight	14.6 Kg



POWER

Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 75W in "ON" Mode

OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, 3D NR, MPEG NR, PIP, POP

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

ACCESSORIES

Kettle Lead / VGA Cable / Screws For Stand / Audio Cable / Remote Control / User Manual



