

IP Cameras

IP sWDR True Day & Night Box camera



VC57WD-IP

- Super Wide Dynamic (sWDR)
- High performance 1/3" Sony Double Scan CCD
- Easy-to-use OSD functions (possible to control locally or remotely)
- IR Sensitive mechanical Day/Night filter system built-in
- Optic photo sensor built-in
 - Privacy masking
- Greatly enhanced Sensitivity of 0.0001 Lux at F1.2
- 12VDC/PoE
 - Camera ID
- Optic photo sensor built-in
 - Digital zoom(1x ~ 3x)
- Digital Slow Shutter (DSS)
- Support various network protocol
TCP/IP, DHCP, HTTP, UDP, UPnP, FTP, SMTP, RTP, RTSP, QoS, SSL
- MPEG4 and MJPEG, Max. 30fps/VGA
 - 10/100 Base-T(RJ-45), Wi-Fi(option)
- Full duplex Audio support(option)

IP Box camera



VC56H-IP

- 1/3" Sony Super HAD CCD II
- 0.00001Lux extreme low light sensitivity
- 3 DNR Noise elimination
- 12VDC/PoE
- Support various network protocol
TCP/IP, DHCP, HTTP, UDP, UPnP, FTP, SMTP, RTP, RTSP, QoS, SSL
- MPEG4 and MJPEG, Max. 30fps/VGA
- 10/100 Base-T(RJ-45), Wi-Fi(option)
- Full duplex Audio support(option)
- Surge voltage input protection built-in

IP Dome camera



VD101H-IP

- 1/3" Sony Super HAD CCD II
- 0.00001Lux at F1.2(Sens-up : remarkable low light performance)
- 3 DNR Noise elimination
 - HSBLC(Highlight Suppression BLC)
- Privacy zone (8 zones)
 - Motion detection (4 zones)
- RS-485 remote control(Pelco-D)
 - Multi-lingual OSD menu
- 12VDC
 - Tool-free 3-Axis
 - Tool-free installation
- Support various network protocol
TCP/IP, DHCP, HTTP, UDP, UPnP, FTP, SMTP, RTP, RTSP, QoS, SSL
- MPEG4 and MJPEG, Max. 30fps/VGA
- 10/100 Base-T(RJ-45), Wi-Fi(option)
- Full duplex Audio support(option)
- Surge voltage input protection built-in