

VH04120P


4CH Professional Embedded DVR, Full D1 Real-Time Recording & Playback, 2U Height Case



Features

- Automatic Upgrade of DVR F/W and Remote S/W
- POS Function up to 4 sets of POS Device
- Quick Setup to designate Recoding Period
- Emergency & intensive Recording
- Dual-Stream with Adjustable fps and Resolution
- Network Bandwidth Control(25Kbps~100Mbps)
- Mobile Viewer by WAP Connetion(2G & 3G Phones)
- Smart Phone Monitoring
- iPhone & iPad & Black Berry & Android & Win Mobile Phone
- Help Message Pop-up just by One Mouse-Click
- Time Synchronization by NTP Server
- Support e-SATA

Dimension



MODEL		VH04120P
Compression	Algorithm	Video : H.264. Audio :G723.1
HDD Bay		3 x SATA HDD or 2 x SATA HDD & 1 x DVD
Operation System		Embedded Linux
Input		4CH
Video	Loop out	Built-in
Video Mode		NTSC/PAL Selectable
Display Speed(NTSC/PAL)		120/100 fps
		2 x Main Monitor (Composite & DVI) &
Video–Out (Monitor)		1 x Spot Monitor (Composite)
Recording Speed (NTSC/PAL)	352x240/288(CIF)	120/100 fps
	720x240/288	
	(Half D1)	120/100 fps
	720x480/576(D1)	120/100 fps
	120X400/010(D1)	NTSC : 352x240, 720x240, 720x480,
Recording Resolution		PAL : 352x288, 720x288, 720x576
		Continuous, Scheduled, Sensor-Activated &
		Motion Detection Recording Pre & Post Alarm
Recording Mod	de	Recording, Emergency Recording, Quick
	Speed	Backup x1, x2, x4, x8, x16, x32
Playback & Search	Speed Plavback	
	-,	1, 4, 9 & 16 Ch Real-Time Playback at CIF
	Channel	(30/25 fps per Ch)
	Function	Intelli-Search by Time Bar, Calendar
Accellentere et / /		(Date & Time) and Event/System Search
Audio Input / Output		4 Ch Input / 1 Ch Output
Alarm Input / Relay Output P/T/Z Control and Port		4 Ch / 4 Ch
		Virtual Joy-Stick Control on screen by Mouse
		Pan/Tilt/Zoom/Focus/Iris, RS-485 Port
LAN		Gigabit Ethernet (RJ45), Fixed IP, DHCP & DDNS
Remote Management	Software	CMS (CentralManager S/W) & MMS (Mobile
		Viewer) & MacViewer (S/W for Mac OS)
	Web (IE)	Live Monitoring, Playback & System
	Internel	Configuration
Backup Device	Internal	DVD Burner (Option)
	External	Local Backup by USB ODD and Network
Sustam Doogvany after Dowar		Backup by CMS
System Recovery after Power		Auto-Reboot and Journaling File System
Failure Advanced Functions		1) Firmulara Lingrada bu LICR & CMC aver
		 Firmware Upgrade by USB & CMS over Network
		 Automatic Upgrade of DVR F/W and Remot S/W from FTP Server
		3) Import & Export of Setting Value, Water-
		Mark, AVI File Backup
		4) Quick Setup to designate Recording Period
		5) HDD SMART Info (Model, Capacity, Bad
		Sector, Temperature, Used Period)
		6) Warning Alarm for System Over-
		7) Help Message for easy setup & Multi-
		Language support
POS		Text-in Based (RS232, USB to Serial support,
		Ethernet) / Display POS Data on Live &
		Playback
e–SATA System Operation		External Storage Device Support
		(SATA Raid Controller)
		Front Button, IR Remote Controller, USB Mouse
		Keyboard (Option
Power		12V x 5A D/C
Operating Temperature and		5~40℃ / 20~80% RH
Humidity		
Dimension (WxDxH)		420 x 428 x 88 (mm)