

## Mi Series Megapixel IP Camera



Driving IP-based physical security  
through global standardization

### VN7xSM3i Night Vision Outdoor IR Camera

H.264 / M-JPEG Dual Stream, 3.0 Megapixel Sony CMOS Sensor, Day/Night, Standard PoE, Night Vision with IR LED's, Motorized Zoom Lens, IPv4 & IPv6 Compatible  
Model: VN7xSM3i



*VN7xSM3i is an outdoor night vision IR camera with more than **50M IR distance**.  
Intelligently designed, the VN7xSM3i provides motorized lens control which allows precise focus and zoom locally or remotely.  
State-of-the-art IR technology includes variable IR output to prevent oversaturation as well as extended IR lifespan.  
IP67 weather proof enclosure and convenient cable managed bracket provides a rugged and installer-friendly solution for any outdoor surveillance application.*

**Conformant with ONVIF Core 1.02.**

## Features

- 3.0 Megapixel 1/2.8" SONY progressive scan CMOS image sensor for excellent image quality
- IP67 rated weather-proof
- Simple and convenient motorized lens control of tele/wide and focus+/- (Simple focus adjustment)
- Remote lens control on the UI
- X12 Optical zoom
- Cable managed bracket



Product info [support@visionhitech.co.kr](mailto:support@visionhitech.co.kr)  
Marketing [vht@visionhitech.co.kr](mailto:vht@visionhitech.co.kr)

- Extended IR life span
- Dual Streaming of H.264 and M-JPEG
- Up to 30 frames per second at all image resolutions
- Supports image resolutions up to Full HD (1920x1080)
- IPv4 & IPv6 compatible
- Integrated motion detection with pre- and post-alarm image/video buffering
- Event-triggered FTP and email upload of still images and videos
- Full Duplex Two-Way Audio Support(Optional)
- Digital PTZ
- UPnP supported
- 1 Port analog video loop-out port
- External microphone input & speaker output connector (Option)
- Terminal block for external sensors devices
- Supports CBR (constant bit rate) and VBR (variable bit rate) modes
- Controllable frame rate
- Video access through any standard Web browser
- Privacy Masking up to 4 areas
- Supports IEEE 802.3af Power over Ethernet injectors, mid- and end-spans
- Integrated HTTP Web server supporting 50 simultaneous user connections
- HTTPS supported (Hyper Text Transfer Protocol Secured)
- Integrated E-Mail, FTP, DDNS and DHCP client
- Extensive CGI API for software integration and remote programming operations
- Includes Windows based IP Installer and License-free 16 channel NVR software

## Specifications

Classification		Specification
General	CPU	32-bit ARM9 RISC CPU up to 533MHz, 32KB I/D-Cache, MMU
	Video Buffer	16Mbyte Video Frame Buffer
	Flash	16 Mbyte Flash Memory
	SDRAM	256Mbyte
Image Pickup	Image sensor	3.0 Megapixel 1/2.8" SONY progressive scan CMOS image sensor
	Total Pixels	2144(H) x 1588(V) 3.4 Megapixel
	Effective Pixels	2096(H) x 1561(V) 3.27 Megapixel
	S/N Ratio	More than 52dB
	Min. Illumination	1 Lux (IR On)
	IR Distance	50M




	Day & Night	ICR
	Lens Control	Motorized Lens Control
	Lens	5~60mm Vari-focal Auto Iris Megapixel Lens
Video	Video compression	H.264 baseline profile, Motion JPEG
	Resolutions	Up to 1920 x 1080
	Frame rate	H.264 Up to 15fps with 1920x1080
		MJPEG Up to 15fps at VGA (Simultaneous dual stream with H.264 15fps @1080p)
	Video streaming	Support multi stream with H.264, MJPEG
		Adjustable frame rate
		VBR/CBR in H.264
	Pan/Tilt/Zoom	Digital PTZ
	Image setting	Day & Night
		ATR-EX(WDR)
		Auto White Balance
Auto Exposure		
Privacy Mask		
Effect - Color, Sharpness, Mirror/V-Flip, etc.		
Output	BNC x1, 1.0Vp-p, 75 ohm Composite Video, NTSC/PAL	
Audio  (Option)	Audio streaming	Two-way, full duplex
	Audio compression	G.711
	Sample Rate	8KHZ
	Data Rate	64Kbps
	Audio input	Microphone input /1 x Line-In (Mono)
	Audio output	Line output/ 1 x Line-Out (Mono)
Serial	Port1	RS-485
	Data Rate	600bps~ 115200bps
Network	Security	Password protection
		User access log
		HTTPS encryption
	Supported protocol	HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP RTSP, RTP, TCP, UDP, ICMP, DHCP
System integration	Intelligent video	Motion detection up to 1920x1080 with 32x24 blocks
	Alarm trigger	Motion detection
		External input/Normal Open/Close Type
	Alarm events	File upload via ftp, e-mail


		Notification via email, FTP and TCP
	Video buffer	16MB pre-alarm and post-alarm
	Firmware upgrade	Remote upgrade via network
	API	CGI Interface document
		ActiveX Interface(ocx(dll) + document)
etc	RESET Button	1 x Factory Reset Button
Physical	Power Source	DC 12V/1.5A, PoE(Power over Ethernet): 802.3af
	Power Consumption	Max. 7.8W, Max. 12.6W with IR On
	Net Weight	1500g (Camera Only)
	LED's	Network Connection
	Dimension	101mm(W) X 108.7mm(H) X 297mm(D) including Bracket
Environment	Operating Temperature	-25 degree~50 degree Celsius(-13F~122F)
	Storage Temperature	-25 degree~60 degree Celsius(-13F~140F)
Software	Included Software	NVR Lite (16 Channel), IP Installer (Windows only)
Package	Package Contents	Network Camera, Use Manual, External Power Adaptor, Software CD

■ Specifications are subject to change without prior notice to enhance performance and stability

## Dimension



## Connectors



**VISION**

Product info [support@visionhitech.co.kr](mailto:support@visionhitech.co.kr)  
Marketing [vht@visionhitech.co.kr](mailto:vht@visionhitech.co.kr)