

PT-Series Network Video Recorders (NVRs)

Wavestore PT-Series server/ storage NVRs deliver a recording, management and control solution for small and medium size security and video surveillance projects.

Typically, at least 48 network cameras can be connected to each NVR, which are supplied preinstalled with Wavestore's Video Management Software (VMS). Housed in a compact mini-tower case, suitable for desktop or shelf mounting, PT-Series NVRs can accommodate up to 4 x 3.5" hot swappable hard drives to provide up to 40TB of storage. This can deliver 45 days continuous real-time recording from 48 Full HD cameras in a typical installation**.

WaveView client software can be run straight from the NVR to monitor live or recorded video, making it an ideal single-box solution. The PT-Series has a throughput of up to 300Mbits/sec and comes with dual network interfaces to segregate incoming and outgoing network traffic. The ports can be bonded to provide fault-tolerance for perfect performance at all times.

Choose your Wavestore VMS channel license level

PT-Series NVRs are compatible with all four levels of Wavestore's VMS: Base, Premium, Enterprise and Ultimate, which offer a broad range of capabilities and features to ensure the right solution for any given application.

Server Groups

Multiple PT-Series NVRs, as well as other Wavestore NVRs and HVRs, can be configured into a server group of up to 255 units* to satisfy large and distributed installations via a single Graphical User Interface (GUI).

EcoStore energy saving

PT-Series NVRs are compatible with Wavestore's unique EcoStore[™] technology at Enterprise channel license level and above, which can save over 80% of HDD energy by spinning down drives

not in a read or write state.

Warranty

All PT-Series NVRs are supplied with a full three-year return to base hardware warranty, extendable to five years.



Pre-installed with Wavestore Video Management Software (VMS)

Whether you are looking for a video only application using a mix of camera technologies, including 360° fisheye and 4K, or a fully integrated solution with third-party providers for Access Control, Video Analytics, Intruder Detection and more, it is possible to create best-in-breed total security solutions that meet exacting specifications for the end-customer with Wavestore's ONVIF conformant truly open-platform VMS.

Coupled with a flexible and cost-effective license model, additional cameras or functionality can easily be added at a later date without disruption to the existing system.

What's more, there's no recurring support contracts to sign up to and technical support is free of charge.

Wavestore's WaveView and WaveView Mobile clients

WaveView is Wavestore's free of cost client software which delivers an intuitive interface designed to offer full, yet simple, control of total security solutions. Authorised WaveView client devices can simply access individual or grouped Wavestore NVRs to give users full control of their security system.

The WaveView Mobile application adds mobile viewing capability enabling operators to view and control their system from iOS or Android devices.

WaveView's leading search and playback capabilities allow operators to quickly review recorded images via an intuitive play bar, providing instantaneous access to exactly the right image from any point in time from the recorded data, even over large amounts of stored data.

Export of video evidence

In just three mouse clicks, operators can export clips from multiple cameras simultaneously to a variety of file formats or create a storyboard of events with a sequence of cameras, including virtual PTZ control of 360° fisheye cameras. Authentication and encryption of video and audio content are also supported.

At a glance

Camera channels Typically 48 IP

Hard drives Up to $4 \times 3.5''$

Storage capacity Up to 40TB

IP throughput Up to 300Mbits/s WaveView client operation from the NVR EcoStore[™] HDD spin-down ready*

Key Features

- Highly secure VMS embedded into the Linux Operating System (OS)
- Up to 4096bit encryption with comprehensive cyber-security package provided as standard
- Fully ONVIF conformant and truly open-platform
- Compatible with the world's leading camera brands and video formats
- Compatible with a wide range of camera technology including UHD, 4K, HD, 360° fisheye, panoramic, thermal, HD over analogue and analogue
- Comprehensive third-party integration capability across Intelligent Video Analytics, Access Control, Intruder Detection and other technologies*

* These features are available from the NVR/ HVR but are dependent on the Wavestore VMS channel license level to operate. Please check specifications prior to ordering.

** Typical expected figures; please make sure the calculations for your specific camera and site requirements are completed before ordering.

PRODUCT DATASHEET	
PT-Series Network Video Recorders (NVRs)	



TECHNICAL SPECIFICATION	PT-Series				
Channels & throughput					
Typical no. IP channels	48				
Max. built-in analogue channels	-				
Typical no. audio channels	48				
Max. IP throughput	300Mbits/sec				
Compression formats	H.265, H.264, MJPEG, MPEG-4, MxPEG and JPEG2000				
Typical video storage rate	600 FPS				
Operation					
Operating system	Linux (VMS embedded)				
Operating system drive	64GB SATA DOM				
CPU	Intel i5 6400				
RAM	8GB DDR4 ECC				
Graphics card	NVIDIA GeForce GT1030				
Connectivity					
Network interfaces	2 x Gb NIC				
USB ports	2 x USB 2.0 2 x USB 3.0				
Monitor outputs (connect one only)	DVI-I HDMI				
Alarm I/O module	Optional				
Keyboard and mouse	Yes (not supplied)				
Wavestore VMS					
Pre-installed with Wavestore's VMS	Yes				
Wavestore VMS channel license compatibility	All levels				
VMS configuration restore points	Yes				
Multicast support	Yes				
Automatic camera discovery and camera group set-up	Yes				
WaveView Client					
Local client use	Yes (up to 15Mbits/sec)				
Remote client use	Yes				
WaveView Mobile compatible	Yes				

TECHNICAL SPECIFICATION	PT-Series					
Storage and Hard Drives (HDDs)						
Max. number of HDDs	4					
Min. internal storage	4TB					
Max. internal storage	40TB					
HDD type	Surveillance grade (standard) Enterprise grade (option)					
Hot swap HDD bays	Yes					
EcoStore™ HDD spin-down compatible*	Yes					
Redundancy						
RAID	-					
Dual PSU	-					
Failover compatible	-					
Physical						
Form factor	Mini Tower					
Dimensions (D x W x H)	280mm x 210mm x 240mm					
Weight (with 1 HDD fitted)	5.7kg (approx.)					
Weight (each additional HDD)	Approx. 750g					
Operating temperature range	5°C to 40°C 41°F to 104°F					
Operating relative humidity (non-condensing)	20% - 80%					
Power						
Power input	100-240v AC 50/60Hz					
Power consumption with 1HDD	100W typical					
Power consumption (each additional HDD)	9W typical					
Warranty						
Standard warranty	3-year return to base					
Extended warranty	Up to 5-years					

Rear Panel Connections:

HDMI port	•	2
DVI-I port	•	2 :
Network interface Ports 0,1	•	Μ

^{• 2} x 3.0 USB ports

- 2 x 2.0 USB ports
- Mains input

Popular configurations:

PT4-8PU1-NR-2G-NA-S11 PT4-20PU2-NR-2G-NA-S11 PT4-40PU4-NR-2G-NA-S11 Mini tower NVR, 8TB storage, 300Mbps, EcoStore ready, 3-year warranty Mini tower NVR, 20TB storage, 300Mbps, EcoStore ready, 3-year warranty Mini tower NVR, 40TB storage, 300Mbps, EcoStore ready, 3-year warranty

.

•

Build your PT-Series NVR:

Series	Form Factor	Max No. of HDDs	Storage fitted (TB)	Drive type fitted	No. of HDDs fitted	RAID ports	No. of NICs	Analogue channels	Power supply	CPU options	Graphics options
Р	T (Tower)	4	From 4TB to 40TB in multiples of 4TB, 6TB, 8TB, or 10TB	PU (Surveillance grade) GD (Enterprise grade	1 to 4	NR (none)	2G (2)	NA (none)	S (single)	1 (standard)	1 (standard)



Email: info@wavestore.com Visit: wavestore.com

Specifications may change without notice. Version: WST-0065-06 GLOBAL HQ (EMEA) Wavestore Global Ltd. Tel: +44 (0) 1895 527 127 USA/CANADA Wavestore Americas Inc. Toll-free: 855-526-8887

Channel licenses sold separately

NVIF | The IP-based Security Standard

MIDDLE EAST Wavestore Middle East Tel: +971 (4)881 2903